
Subject: Re: up & down within ColumnList moves focus out

Posted by [mirek](#) on Wed, 25 Nov 2009 10:39:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

bonami wrote on Tue, 24 November 2009 20:46 Draw::GetStdFontCy() = 0

Mirek, if this is my own system's fault, maybe there is no need to further investigate on it. It's a stripped system, thus not so trustable.

That might be a reason, but not excuse

U++ should work even on stripped system.

The query for system font is in Draw/FontWin32:

```
void GetStdFontSys(String& name, int& height)
{
#ifdef PLATFORM_WINCE
    name = "Arial";
    height = 10;
#else
    NONCLIENTMETRICS ncm;
    ncm.cbSize = sizeof(ncm);
    ::SystemParametersInfo(SPI_GETNONCLIENTMETRICS, sizeof(ncm), &ncm, 0);
    name = FromSystemCharset(ncm.lfMenuFont.lfFaceName);
    height = abs((int)ncm.lfMenuFont.lfHeight);
#endif
}
```

put logs there:

```
void GetStdFontSys(String& name, int& height)
{
#ifdef PLATFORM_WINCE
    name = "Arial";
    height = 10;
#else
    NONCLIENTMETRICS ncm;
    ncm.cbSize = sizeof(ncm);
    ::SystemParametersInfo(SPI_GETNONCLIENTMETRICS, sizeof(ncm), &ncm, 0);
    name = FromSystemCharset(ncm.lfMenuFont.lfFaceName);
    height = abs((int)ncm.lfMenuFont.lfHeight);
    DDUMP(name);
    DDUMP(height);
#endif
}
```

and/or perhaps try

```
void GetStdFontSys(String& name, int& height)
{
#ifdef PLATFORM_WINCE
    name = "Arial";
    height = 10;
#else
    NONCLIENTMETRICS ncm;
    ncm.cbSize = sizeof(ncm);
    ::SystemParametersInfo(SPI_GETNONCLIENTMETRICS, sizeof(ncm), &ncm, 0);
    name = FromSystemCharset(ncm.lfMenuFont.lfFaceName);
    height = abs((int)ncm.lfMenuFont.lfHeight);
    if(height == 0) {
        name = "Arial";
        height = 10;
    }
#endif
}
```

Mirek
