

---

Subject: Meaning of BUGLOG

Posted by [michael](#) on Wed, 30 May 2007 07:52:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

My application creates a .BUGLOG File with the following content:

\* C:\Programme\prohibisZA3\prohibisZA.exe 30.05.2007 09:11:58, user: Michael

0 ms: select substring\_index(USER(), '@', 1)

0 ms: SELECT \* FROM prohibisZA\_Kunden WHERE PRODUKT = 'prohibis' ORDER BY NAME

0 ms: SELECT COUNT(\*) FROM prohibisZA\_Kunden

0 ms: select substring\_index(USER(), '@', 1)

0 ms: SELECT \* FROM prohibisZA\_Kunden WHERE PRODUKT = 'prohibis' ORDER BY NAME

0 ms: SELECT COUNT(\*) FROM prohibisZA\_Kunden

0 ms: SELECT \* FROM prohibisZA\_Server WHERE GESELLSCHAFTER = '197100' ORDER BY FUNKTION

0 ms: SELECT COUNT(\*) FROM prohibisZA\_Server

0 ms: SELECT \* FROM prohibisZA\_Kunden WHERE PRODUKT = 'prohibis' ORDER BY NAME

0 ms: SELECT COUNT(\*) FROM prohibisZA\_Kunden

Are these errors? It seems that every SQL-Query is written in this BUGLOG. My application seems to work fine.

Michael

---

---

Subject: Re: Meaning of BUGLOG

Posted by [mirek](#) on Wed, 30 May 2007 09:06:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Well, this is most likely a bug in u++.

There is a feature in U++ that tracks sql statments that take too long -> this can indicate unoptimal data model, e.g. missing index.

It looks like that for your application, the time threshold is for whatever reason set to 0ms. What database are you using?

---

---

Subject: Re: Meaning of BUGLOG

Posted by [michael](#) on Wed, 30 May 2007 09:27:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I'm using MySQL 5.41 on Windows XP and Windows Server 2003. The BUGLOG is only created on the Windows 2003 Machine.

How can i set the time threshold?

Michael

---

---

Subject: Re: Meaning of BUGLOG  
Posted by [michael](#) on Fri, 01 Jun 2007 10:54:29 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Does anybody has any ideas on how to solve this problem?

Michael

---

---

Subject: Re: Meaning of BUGLOG  
Posted by [michael](#) on Sat, 02 Jun 2007 17:49:56 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Solved it.

Seems that it was caused by the way i was accessing a function for doing some sql-queries.

This function is member of my main-class which i made global because i wanted to access this sql-function from another class.

Now i changed the way how i access my sql-function from the other class by creating an instance of my main-class within this function.

Sounds complicated... but i just wanted to say more than SOLVED without an explanation for further visitor with problems like this.

Michael

---