
Subject: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d

Posted by [nietzfock](#) on Thu, 12 Mar 2015 17:15:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

"ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d"...¿why?
why the code throws the error?

```
void iniciarConeccion(char nombreMaquina[],char paisMaquina[]){  
char respuesta1[]="vacio";  
char respuesta2[]="vacio";  
WSAStartup(MAKEWORD(2,2), &wsa);
```

```
Winsock=WSASocket(AF_INET,SOCK_STREAM,IPPROTO_TCP,NULL,(unsi gned  
int)NULL,(unsigned int)NULL);  
host = gethostbyname("localhost");  
localIP = inet_ntoa (*(struct in_addr *)*host->h_addr_list);
```

```
direc.sin_addr.s_addr = inet_addr(localIP);  
direc.sin_family=AF_INET;  
direc.sin_port=htons(999);
```

```
if(Winsock==INVALID_SOCKET)  
{PromptOK("ERROR ");}
```

```
if((WSAConnect(Winsock,(SOCKADDR*)&direc,sizeof(direc),N  
ULL,NULL,NULL,NULL))==SOCKET_ERROR){  
String error=MensajeError(GetLastError());  
PromptOK(error);  
}
```

```
fromlen=sizeof(direc);  
while(strcmp(respuesta1,"vacio")==0){  
if(sendto(Winsock,nombreMaquina,sizeof(nombreMaquina),0,(str uct sockaddr *)&direc,  
sizeof(direc))== -1)  
{  
PromptOK("ERROR");  
}  
_sleep(5000);  
recvfrom(Winsock,respuesta1,sizeof(respuesta1),0,&addr,& amp;fromlen);  
} //system("PAUSE");  
while(strcmp(respuesta2,"vacio")==0){  
sendto(Winsock,paisMaquina,sizeof(paisMaquina),0,(struct sockaddr *)&addr, sizeof(addr));  
{  
PromptOK("ERROR");}  
_sleep(5000);  
recvfrom(Winsock,respuesta1,sizeof(respuesta1),0,&addr,& amp;fromlen);
```

```
}  
WSACleanup();  
  
}
```

Subject: Re: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d
Posted by [koldo](#) on Fri, 13 Mar 2015 09:02:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello nietzfock

It would be better if you include all the code (in a reduced form) and indicate where that message appear. Anyway, probably the place is here:
String error=MensajeError(GetLastError());
PromptOK(error);
Could you send us the raw message?

Subject: Re: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d
Posted by [nietzfock](#) on Fri, 13 Mar 2015 15:38:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

yes, you have reason the message here ("invaled utf-8 sequence: n Ya que el equipo d").
¿Why?. What am I doing wrong?.

PD: sorry but my English is very bad

Subject: Re: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d
Posted by [koldo](#) on Mon, 16 Mar 2015 08:52:09 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello nietzfock

Your code is incomplete, and there are many variables undeclared, so I imagine they are global variables. I have tried to make it work and I have replaced MensajeError() with GetErrorMessage().

The error message got is:
No se puede establecer una conexión ya que el equipo de destino denegó expresamente dicha conexión.
The error is the WSAECONNREFUSED (10061). There is an explanation here, and the reason usually is that your trying to connect to an address and a port where nobody is listening.

Subject: Re: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d
Posted by [nietzfock](#) on Tue, 17 Mar 2015 17:36:19 GMT
[View Forum Message](#) <> [Reply to Message](#)

thank you very much.

Subject: Re: ERROR: INVALID UTP-8 SEQUENCE: n Ya que el equipo d
Posted by [koldo](#) on Wed, 18 Mar 2015 16:17:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello Nietzfock

You are welcome!

If you fill more comfortable you can also make your questions in your language. I would translate them for all to my simple () English.
