

---

Subject: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Sat, 06 May 2006 12:56:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

how can be seen in the following picture the numbers are not aligned vertically although each row has been formatted and contains always the same numbers of chars.


If I could use the Courier font the problem would disappear. Unfortunately I was not able (I used even Navigate...) to found something useful to set the font and maybe the color.

A workaround is to use label inside each cell. Another is to assign a new column to the number but I do not like the vertical line between the name and the number.

Luigi

## File Attachments

1) [arrfont.png](#), downloaded 1343 times



The screenshot shows a software interface for a chess tournament. At the top, there are controls for 'Show Round' (set to 1), 'Current Round', and buttons for 'Modify Pairing', 'Improve Colors', 'Load Results', and 'Update CrossTable'. Below is a table with columns: Board, White Player, Black Player, IDW-IDB, code, and Result. A red circle highlights the '(0.0)' rating for Karpov, Alexander in row 2.

Board	White Player	Black Player	IDW-IDB	code	Result
1	Karpov, Vadim (0.0)	Karpova, Luba (0.0)	2 - 13	1	1 - 0
2	Karpov, Alexander (0.0)	Polikarpov, Evgeni (0.0)	3 - 12	0	0 - 1
3	Karpov, Igor (0.0)	Karpov, Petr (0.0)	4 - 11	1	1 - 0
4	Karpov, Viktor (0.0)	Karpov, Alexey (0.0)	5 - 10	0	0 - 1
5	Karpov, Vladimir (0.0)	Karpova, Lyudmila (0.0)	6 - 9	1	1 - 0
6	Karpovich, Andrey (0.0)	Karpov, Andrey Ivan. (0.0)	7 - 8	0	0 - 1
7	Karpov, Anatoly (0.0)	BYE (0.0)	1 - 0	1	1 - 0

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [fudadmin](#) on Sat, 06 May 2006 13:10:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I guess something like this could be helpful:

<http://www.arilect.com/upp/forum/index.php?t=msg&th=234& amp;start=0&>

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [fudadmin](#) on Sun, 07 May 2006 11:00:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

One more idea. What if to use composite ctrl (2 labels inside one cell?) once again?

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Sun, 07 May 2006 12:45:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

fudadmin wrote on Sun, 07 May 2006 13:00 One more idea. What if to use composite ctrl (2 labels inside one cell?) once again?

I thought about one label for cell and set the font courier. But your idea seems better because I can format each of them in different manner (style and color)... yes, good idea

This time the composite widget should not be a problem because I do not need to retrieve data.

But I am afraid of the array cursor that could be not aware that I clicked on the label.

Ok, I'll do some experiment... but gime ve time and I'll post a test case.

BTW, is there a label that can be formatted in QTF? I couldn't found it. Perhaps should be easy to do it spying in the code of some Prompt method in which the QTF string can be set.

Luigi

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Sun, 07 May 2006 17:44:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

forlano wrote on Sun, 07 May 2006 14:45 This time the composite widget should not be a problem because I do not need to retrieve data. But I am afraid of the array cursor that could be not aware that I clicked on the label.

Ok, I'll do some experiment... but gime ve time and I'll post a test case.

Luigi

Well, I was too optimistic .

You can see how it looks the twolabel widget. It is very nice (I would add the national flag of the player one day), but the array cursor as usual is unsensitive to the click on the embedded ctrl. So when the array is covered by label I hope to move this damned cursor.

Moreover, and most important, I was not able to set these labels as I wanted! You can see the two edits that wait to be sent in the twolabel widget and then in the array but the callback is absent I attach the code, maybe some volunter will retouch it. So we returned again on the set method of the previous thread. If I can see how work the "Set" maybe I'll catch the "Get" one.

Thank you

```
#include <CtrlLib/CtrlLib.h>
```

```
#define LAYOUTFILE <twolabelwidget/a.lay>
```

```
#include <CtrlCore/lay.h>
```

```
//----- begin class -----  
class TwoLabel : public WithTwoLabel<ParentCtrl> {  
String str1;  
String str2;  
public:  
typedef TwoLabel CLASSNAME;  
void WriteLabel(String s1, String s2);
```

```

TwoLabel();
};

void TwoLabel::WriteLabel(String s1, String s2) //should be the Constructor?
{ str1 = s1;
  str2 = s2;
}

TwoLabel::TwoLabel()
{ CtrlLayout(*this);
  str1 = "left";
  str2 = "right";
  lbl1.SetLabel( str1 );
  lbl2.SetLabel( str2 );
}

void Extra2(One<Ctrl>& ctrl)
{ ctrl.Create<TwoLabel>();
}
//----- end class -----

//----- begin class MyApp-----
class MyApp : public TopWindow {
  TopWindow w;
  ArrayCtrl arr;
  Button btn;
  EditString edit1, edit2;
public:
  typedef MyApp CLASSNAME;
  MyApp();
  void SetIntoArray();
};

void MyApp::SetIntoArray()
{ TwoLabel twolbl;
  String s1, s2;
  s1 = ~edit1;
  s2 = ~edit2;
  arr.Add("aaa", Null/* ??? */);
}

MyApp::MyApp()
{ Add(arr);
  arr.SizePos();
  arr.AddColumn("col1",20);
  arr.AddColumn("col2",20).Ctrls(Extra2);
  arr.SetLineCy(20);
}

```

```

arr.Add("aaa");
arr.Add("bbb");
arr.Add("ccc");
arr.Inserting(true);
Add(edit1);
Add(edit2);
edit1.LeftPosZ(48, 76).TopPosZ(280, 19);
edit2.LeftPosZ(140, 76).TopPosZ(280, 19);
Add(btn);
btn.SetLabel("set into array").LeftPosZ(236, 88).TopPosZ(280, 20);
    btn.WhenAction = THISBACK(SetIntoArray);
}
//----- end MyApp -----

```

```

GUI_APP_MAIN
{ MyApp a;
  a.Sizeable().Run();
}

```

```

//////////
layout file: a.lay

```

```

LAYOUT(TwoLabel, 188, 20)
  ITEM(Label, lbl1, SetFont(StdFont(13).Bold()).SetInk(SLtBlue).LeftPosZ(4,
128).VCenterPosZ(17, 1))
  ITEM(Label, lbl2,
SetAlign(ALIGN_CENTER).SetFont(StdFont(13).Bold()).SetInk(SLtRed).LeftPosZ(132,
56).VCenterPosZ(17, 1))
END_LAYOUT

```

## File Attachments

---

1) [swiss4.jpg](#), downloaded 1730 times

col1	col2	
aaa	left	right
bbb	left	right
	left	right
	left	right
ccc	left	right

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [mirek](#) on Sun, 07 May 2006 17:53:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

forlano wrote on Sat, 06 May 2006 08:56Hello,

how can be seen in the following picture the numbers are not aligned vertically although each row has been formatted and

If they look "vertically unaligned", it is decision of font designer, not U++ - it does vertical centering based on font height (in StdDisplay, which is relevant here).

Mirek

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Wed, 28 Jun 2006 16:45:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

Let's come back on this old topic about font and arrayctrl.

Here <http://www.arilect.com/upp/forum/index.php?t=msg&th=234&start=0> we've seen how powerful is the singleton technique and how it is used in conjunction with SetDisplay to set the color of a cell/column.

The question now is: can the same technique be applied to change the font (to courier for example) of one column of the arrayctrl?

I do not need to change the font of the overall application, but only locally in the arrayctrl.

Luigi

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [mirek](#) on Thu, 29 Jun 2006 18:16:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

forlano wrote on Wed, 28 June 2006 12:45Let's come back on this old topic about font and arrayctrl.

Here <http://www.arilect.com/upp/forum/index.php?t=msg&th=234& amp; amp;start=0&> we've seen how powerful is the singleton technique and how it is used in conjunction with SetDisplay to set the color of a cell/column.

The question now is: can the same technique be applied to change the font (to curier for example) of one column of the arrayctrl?

I do not need to change the font of the overall application, but only locally in the arrayctrl.

Luigi

Tehchnical note: It is not singleton what is powerful here. Display does not have to be singleton, often it is not.

And yes, you can of course use Display to change the font. Alternatively, you can use AttrText as Value to do the same.

Mirek

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Sat, 01 Jul 2006 07:38:46 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

luzr wrote on Thu, 29 June 2006 20:16

And yes, you can of course use Display to change the font. Alternatively, you can use AttrText as Value to do the same.

Mirek

I believed it was easy, and maybe it is, but I was unable to set the font of the column of the array. Below there is the code that set in red some cell of the arrayctrl. Does anybody know how to modify it to set the font, say Courier, of the column using one of the method listed above by Mirek? Thanks a lot.

Luigi

```
#include <CtrlLib/CtrlLib.h>
```

```
class NumbersOnRed : public Display
```

```
{  
public:  
    static bool numberString(String s);  
    void PaintBackground(Draw& w, const Rect& r, const Value& q,  
                        Color ink, Color paper, dword style) const;
```

```
};
```

```
bool NumbersOnRed::numberString(String s)
```

```
{  
    if(s.GetCount() == 0)  
        return false;
```

```
    int i = 0;  
    if(s[0] == '+' || s[0] == '-')  
        i++;
```

```
    while(i < s.GetCount() && s[i] >= '0' && s[i] <= '9')  
        i++;
```

```
    return i == s.GetCount();
```

```
}
```

```
void NumbersOnRed::PaintBackground(Draw& w, const Rect& r, const Value& q,  
                                   Color ink, Color paper, dword style) const
```

```
{  
    if(!IsNumber(q) || (!IsString(q) && numberString(AsString(q))))  
        paper = Color(255, 150, 150);
```

```
    Display::PaintBackground(w, r, q, ink, paper, style);
```

```
}
```

```
GUI_APP_MAIN
```

```
{  
    ArrayCtrl array;  
    array.AddColumn("value").SetDisplay(Single<NumbersOnRed>());  
    array.Add("test1");  
    array.Add("2test");  
    array.Add("3 test");  
    array.Add("4");
```

```
array.Add("test");
array.Add("-99");
TopWindow win;
win.Zoomable().Sizeable();
win.Add(array.SizePos());
win.Run();
}
```

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [mirek](#) on Sun, 09 Jul 2006 14:04:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Please check reference/Display.

If all you need is different font, you can also use

```
AttrText("My cell text").SetFont(Courier(14));
```

as the value you put inside the ArrayCtrl.

Mirek

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [forlano](#) on Mon, 10 Jul 2006 13:46:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

luzr wrote on Sun, 09 July 2006 16:04 Please check reference/Display.

It does work!

Let me show the steps done for the next generations:

1. create a column of the arrayctrl in this way:

```
arrp.AddColumn("wname", "White Player", 19).SetDisplay(Single<FontDisplay>());
```

Here should be noted the SetDisplay() method that does the job.

2. Create the following singleton ( ) derived by Display:

```
struct FontDisplay : Display {
    virtual void Paint(Draw& w, const Rect& r, const Value& q, Color ink, Color paper, dword style)
```

```
const
{
Font fnt = Courier(14);
String txt = AsString(q);
w.DrawRect(r, paper);
w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
}
};
```

Of course one may want to set a different foreground color (ink), different font size and so on.

Quote:

If all you need is different font, you can also use

```
AttrText("My cell text").SetFont(Courier(14));
```

as the value you put inside the ArrayCtrl.

Mirek

I've not understood what to do in this last case, but it doesn't matter. For today it's enough. Now I want to study the singleton to really understand what I've done

Luigi

---

---

Subject: Re: Is it possible to set the Font type for the arrayctrl?

Posted by [mirek](#) on Mon, 10 Jul 2006 15:31:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

```
arrp.Add(AttrText("My cell text").SetFont(Courier(14)));
```

Mirek

---