
Subject: Re: Limitation in Format() function?
Posted by [mirek](#) **on Fri, 18 Jan 2008 14:28:29 GMT**
[View Forum Message](#) <> [Reply to Message](#)

alex100 wrote on Fri, 18 January 2008 06:02Hi

I am trying to send an SQL command to SQLite database and I am building it using the Format function. Target database table has lots of fields.

IF I use more than ten % in the first argument of the Format function and error appears like this:

```
error: invalid conversion from `const char*' to `int'  
error: initializing argument 1 of `Upp::String Upp::Format(int, const char*,Upp::Value, Upp::Value,  
Upp::Value,Upp::Value, Upp::Value, Upp::Value, Upp::Value, Upp::Value, Upp::Value, Upp::  
Value)'
```

Example:

```
This works: strSQL=Format("( ...)  
%d,%0.2d-%0.2d-%0.2d','%s',%d,'%s','%0.2d-%0.2d-%0.2d')",1,2008,1,1,  
"aaa",1,"aaa",2008,1,1);
```

```
This doesn't work: strSQL=Format("( ...)  
%d,%0.2d-%0.2d-%0.2d','%s',%d,'%s','%0.2d-%0.2d-%0.2d',%d)",1,2008,1,1,  
"aaa",1,"aaa",2008,1,1,1);
```

Is that a limitation?

Alex

Yes, currently, Format is limited to 10 parameters. Adding more is simple, but slightly increases the size of any linux binary using Format...

You can also use:

```
String Format(const char *s, const Vector<Value>& v);
```

- that has no limit at all.

Should I increase the limit?

Mirek