
Subject: Re: Problem Building Sample Applications
Posted by [bytefield](#) on Sun, 27 Jan 2008 10:31:07 GMT
[View Forum Message](#) <> [Reply to Message](#)

mr_ped wrote on Sun, 27 January 2008 11:31
(almost everybody here does use [drive:]\\upp which works well)
i use /usr/bin/theide and /home/can/upp

Quote:

```
C:\WATCOM\H\NT\objidl.h(1074) : error C2061: syntax error : identifier 'PRPC_MESSAGE'  
C:\WATCOM\H\NT\objidl.h(1076) : error C2061: syntax error : identifier 'PRPC_MESSAGE'  
C:\WATCOM\H\NT\objidl.h(1076) : fatal error C1003: error count exceeds 100; stopping  
compilation
```

Seems Watcom use H folder for include files. Check Theide configuration to see if there is no reference to that path.

Or if you have used Watcom compiler to build examples, set in Build Methods.. MinGW as default. However, why do you use Watcom Compiler? It is not good at all, and miss more languages features. I know it from when i used it on Windows, now on Linux gcc(g++) is the best. So using MinGW is the best (second) choice. First one is M\$ Compiler, which is optimized for exe format only. The MinGW comes with Upp or you can download latest version from it site and also MS give a free version of his compiler, so you can use booth.
