
Subject: Japanese IME test code

Posted by [mobilehunter](#) on Mon, 31 Mar 2008 07:58:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hope Mirek and other can check these code

```
case WM_IME_STARTCOMPOSITION:
```

```
{
    HWND hwnd =GetHWND();
    POINT pt;
    GetCaretPos(&pt);// I don't know the properway to get this in UPP way.
    HIMC hIMC = ImmGetContext(hwnd);
    COMPOSITIONFORM cf;
```

```
/*These lines up to us to make ime font match to current font, or just the font size.
```

```
FontInfo fi = Draw::GetStdFont().Info();
LOGFONT lf;
HFONT hfont = fi.GetHFONT(); //i'm sorry to add this function manually to Draw.h, since i don't
know how to get HFONT
GetObject(hfont, sizeof(LOGFONT), &lf);
ImmSetCompositionFont(hIMC, &lf);
```

```
cf.dwStyle = CFS_POINT;
cf.ptCurrentPos.x = pt.x;
cf.ptCurrentPos.y = pt.y;
ImmSetCompositionWindow(hIMC, &cf);
ImmReleaseContext(hwnd, hIMC);
}
break;
```

Above code will make IME window position start at current caret position.

Please fix above codes, since i don't have deep understanding of UPP codes.

Test with GUI17a sample and UWord
