Subject: Re: New functions to SysInfo Posted by koldo on Sun, 10 May 2009 06:50:14 GMT View Forum Message <> Reply to Message

tojocky wrote on Sat, 09 May 2009 22:01Hello Koldo!

Yes, You understand me correct!

I want to handle the shortcut key when the GoogleTranslator is running (is in tray or opened main window).

For the first I would like to handle the shortcut [Ctrl]+[C]+[C] or [Ctrl]+[Ins]+[Ins] . With this handle I can read from buffer the copied text and translate this.

If I'm wrong, please correct me.

If you can give me a simple example about this, i will be glad!

Thank you Koldo!

Hello tojocky

```
You can use this
CONSOLE_APP_MAIN
{
TimeStop t;
int t_ctrl_l, t_ctrl_r;
t_ctrl_r = t_ctrl_l = 0;
while (true) {
 char ctrl_l = (char)GetKeyState(VK_LCONTROL);
 if (ctrl_I & 128) // Left Ctrl pressed
 t_ctrl_l = t.Elapsed();
 char ctrl_r = (char)GetKeyState(VK_RCONTROL);
 if (ctrl r & 128) // Right Ctrl pressed
 t_ctrl_r = t.Elapsed();
 if (t ctrl r - t ctrl | < 300 \&\& t ctrl r - t ctrl | > 0) {
 puts("Voila");
 t ctrl r = t ctrl l = 0;
 }
 Sleep(100);
}
```

This will out a "Voila" when a Ctrl left and a Ctrl right are pressed.

For a Gui application remove the while loop and the Sleep() and put this in a Timer function.

Page 2 of 2 ---- Generated from U++ Forum