
Subject: Re: XmlParser and <![CDATA[
Posted by [mirek](#) on Mon, 11 May 2009 06:37:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

ParseXML has second parameter that, in default form, makes it ignore anything but tags.

You can put there 0 to get all info from XML. Note, however, that in that case initial <? item also qualifies, so you can no longer use n[0].

```
#include <Web/Web.h>
```

```
using namespace Upp;
```

```
CONSOLE_APP_MAIN
```

```
{  
    HttpClient client;  
    client.URL("http://losangeles.craigslist.org/search/jjj?query=php&format=rss");  
    String out = client.ExecuteRedirect();  
    XmlNode n = ParseXML(out, 0);  
    int q = n.FindTag("rdf:RDF");  
    if(q >= 0) {  
        const XmlNode& channel = n[q];  
        for(int i = channel.FindTag("item"); i < channel.GetCount(); i++) {  
            if(channel[i].GetTag() == "item") {  
                const XmlNode &item=channel[i];  
                int tag = item.FindTag("title");  
                if(tag >= 0) {  
                    const XmlNode& title = item[tag];  
                    for(int j = 0; j < title.GetCount(); j++) {  
                        DUMP(title[j].GetType());  
                        DUMP(title[j].GetText());  
                    }  
                }  
            }  
        }  
    }  
}
```

Mirek
