
Subject: Re: Input value at main ()
Posted by [sergeynikitin](#) on Tue, 25 Aug 2009 14:49:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

My piece of code - can someone correct the it, or maybe for someone, and so it will be useful.

```
#include <plugin/pcr/Pcre.h>
```

```
.....
```

```
.....
```

```
GUI_APP_MAIN
```

```
{
```

```
int argc = CommandLine().GetCount();
```

```
const Vector<String>& argv = CommandLine();
```

```
if((argc >= 1) && ((argv[0]=="/?")||(argv[0]=="h")||(argv[0]=="-h")||(argv[0]=="--help")))
```

```
{
```

```
Cout() << "PrintProject-SV ver "<<projectversion<< "\n\n"
```

```
<< "Command Line Syntax: PrintProject2 --export-tr|--cfg=params.cfg|--help \n"
```

```
<< "  --cfg=filename.cfg - Set alternative config file\n"
```

```
<< "    (/cfg=filename and /c=filename - alternative forms of above command)\n"
```

```
<< "    (filename default in win32.exe folder or at home in POSIX systems)\n"
```

```
<< "\n"
```

```
<< "  --export-tr localizationcode - export localization file to edit runtime localization\n"
```

```
<< "    (for example --export-tr ruru - this export russian localization in Unicode encoding\n"
```

```
<< "    ruru0 - for windows-1250 encoding\n"
```

```
<< "    ruru1 - for windows-1251 encoding\n"
```

```
<< "    ruru2 - for windows-1252 encoding\n"
```

```
<< "    ruru3 - for windows-1253 encoding\n"
```

```
<< "    ruru4 - for windows-1254 encoding\n"
```

```
<< "    ruru5 - for windows-1255 encoding\n"
```

```
<< "    ruru6 - for windows-1256 encoding\n"
```

```
<< "    ruru7 - for windows-1257 encoding\n"
```

```
<< "    ruruA - for iso-8859-1 encoding\n"
```

```
<< "    ruruB - for iso-8859-2 encoding\n"
```

```
<< "    ruruC - for iso-8859-3 encoding\n"
```

```
<< "    ruruD - for iso-8859-4 encoding\n"
```

```
<< "    ruruE - for iso-8859-5 encoding\n"
```

```
<< "    ruruF - for iso-8859-6 encoding\n"
```

```
<< "    ruruG - for iso-8859-7 encoding\n"
```

```
<< "    ruruH - for iso-8859-8 encoding\n"
```

```
<< "    rurul - for iso-8859-9 encoding\n"
```

```
<< "    ruruJ - for iso-8859-10 encoding\n"
```

```
<< "\n\n";
```

```
return;
```

```
}
```

```
if((argc >= 1) && ((argv[0]=="/?")||(argv[0]=="/h")||(argv[0]=="-h")||(argv[0]=="--help"))) {  
    Cout() << "Commandline=\"\"<<argv[0] <<"\"\\n";  
}
```

```
if(argc >= 1) {  
    RegExp regexp1("^(?:--cfg|/cfg|-c)\\=(.*)$",RegExp::MULTILINE);  
    if (regexp1.Match(argv[0])){  
        cfg_filename = regexp1[0];  
        cfg_set = true;  
        Cout() << "CFG_FILE=\"\"<<cfg_filename <<"\"\\n";  
    }  
}
```

.....

.....

Other code

.....

.....

```
}
```
