Subject: RichEdit Questions
Posted by mentaltruckdriver on Mon, 17 Apr 2006 01:03:08 GMT
View Forum Message <> Reply to Message

Greetings:

I have two questions to ask so here I go:

1. How do I switch the RichEdit "ColorPusher" to Null? I switch it to any other color (including Null) and it refuses to compile. (BTW  I'm using the mingw 3.4.2 compiler to compile this.)

Here's the error message:

```
C:/upp_backup/uppsrc/RichEdit/RichEdit.lay: In function `void InitLayout(Ctrl&, L&, D&,
UnitLayout__layid&) [
 with L = WithUnitLayout<TopWindow>, D = WithUnitLayout<TopWindow>]':
C:/upp_backup/uppsrc/CtrlCore/TopWindow.h:207:   instantiated from `void CtrlLayout(T&) [with T
= WithUnitLay
 out<TopWindow>]'
C:/upp_backup/uppsrc/CtrlCore/TopWindow.h:215:   instantiated from `void CtrlLayout(T&, const
char*) [with T
 = WithUnitLayout<TopWindow>]'
C:/upp_backup/uppsrc/CtrlCore/TopWindow.h:221:   instantiated from `void CtrlLayoutOK(T&,
const char*) [with
 T = WithUnitLayout<TopWindow>]'
C:/upp_backup/uppsrc/CtrlCore/TopWindow.h:235:   instantiated from `void
CtrlLayoutOKCancel(T&, const char*)
 [with T = WithUnitLayout<TopWindow>]'
C:\upp_backup\uppsrc\RichEdit\Editor.cpp:266:   instantiated from here
C:/upp_backup/uppsrc/RichEdit/RichEdit.lay:46: error: 'class ColorPusher' has no member named
'SetInk'
RichEdit.icpp
1 file(s) compiled in (0:07.46) 7468 msec/file

There were errors. (1:16.84)
```

2. How do I make the RichEdit read from the Windows Fonts folder and use the fonts there instead of creating two fonts (Times New Roman and Courier)?

Thanks for the help.