
Subject: Re: Universal Makefile

Posted by [chickenk](#) on Sat, 28 Aug 2010 07:22:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

Awesome.

A small bug: I'd like to use the "export" feature, using that syntax (my locale is fr_FR.UTF-8):

```
$ make -f uppbox/lpbuild/Makefile PKG=ide FLAGS="GUI MT" export
```

```
Exporting uppbox/lpbuild/Makefile to Makefile.export ...
```

```
make[1]: [ide] Erreur 1 (ignorée)
```

```
$ cat Makefile.export
```

```
.PHONY:default
```

```
default: all
```

```
$
```

What? That's all? Seems it's missing some content. Next I try to use the C locale:

```
$ export LC_ALL=C
```

```
$ make -f uppbox/lpbuild/Makefile PKG=ide FLAGS="GUI MT" export
```

```
Exporting uppbox/lpbuild/Makefile to Makefile.export ...
```

```
make[1]: [ide] Error 1 (ignored)
```

```
$ cat Makefile.export
```

```
[whole content, so it works]
```

So I suggest the subprocesses are executed with the locale set to C, so that words parsing later works.

UPDATE: I also changed one line for more precise output, so that you understand why yours may differ: line 337, I changed `$(call echo," Exporting makefile to $(EXPORT) ...")` to `$(call echo," Exporting $(filename) to $(EXPORT) ...")`

regards,
Lionel
