
Subject: Re: I cant create EXE file with MnGW compiler

Posted by [baloghi](#) on Wed, 01 Sep 2010 13:34:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

If i build Hellocpp program then The lde output is the next:

```
----- CtrlLib ( GUI GCC32 DEBUG DEBUG_FULL BLITZ WIN32 ) ( 1 / 9 )
BLITZ: LabelBase.cpp Button.cpp Switch.cpp EditField.cpp Text.cpp LineEdit.cpp DocEdit.cpp
ScrollBar.cpp Head
erCtrl.cpp ArrayCtrl.cpp MultiButton.cpp PopupTable.cpp DropList.cpp DropChoice.cpp
Static.cpp Splitter.c
pp FrameSplitter.cpp SliderCtrl.cpp ColumnList.cpp Progress.cpp AKeys.cpp RichTextView.cpp
Prompt.cpp Hel
p.cpp DateTimeCtrl.cpp Bar.cpp MenuItem.cpp MenuBar.cpp ToolButton.cpp ToolBar.cpp
ToolTip.cpp StatusBar.
cpp TabCtrl.cpp TreeCtrl.cpp DropTree.cpp DlgColor.cpp ColorPopup.cpp ColorPusher.cpp
FileList.cpp FileSe
l.cpp FileSelUtil.cpp PrinterJob.cpp Windows.cpp Win32.cpp TrayIconWin32.cpp
TrayIconX11.cpp CtrlUtil.cpp
Update.cpp LNGCtrl.cpp Ch.cpp ChGtk.cpp
C:\MinGW\bin\mingw32-make: invalid option -- c
C:\MinGW\bin\mingw32-make: invalid option -- Y
C:\MinGW\bin\mingw32-make: invalid option -- E
C:\MinGW\bin\mingw32-make: invalid option -- A
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- M
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- N
C:\MinGW\bin\mingw32-make: invalid option -- T
C:\MinGW\bin\mingw32-make: invalid option -- H
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 9
C:\MinGW\bin\mingw32-make: invalid option -- A
C:\MinGW\bin\mingw32-make: invalid option -- Y
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- H
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- U
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- 5
C:\MinGW\bin\mingw32-make: invalid option -- M
C:\MinGW\bin\mingw32-make: invalid option -- E
```

```

C:\MinGW\bin\mingw32-make: invalid option -- 3
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- g
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- a
C:\MinGW\bin\mingw32-make: invalid option -- c
C:\MinGW\bin\mingw32-make: invalid option -- _
C:\MinGW\bin\mingw32-make: invalid option -- E
C:\MinGW\bin\mingw32-make: invalid option -- U
C:\MinGW\bin\mingw32-make: invalid option -- G
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- g
C:\MinGW\bin\mingw32-make: invalid option -- a
Usage: mingw32-make [options] [target] ...

```

Options:

```

-b, -m                Ignored for compatibility.
-B, --always-make      Unconditionally make all targets.
-C DIRECTORY, --directory=DIRECTORY
                        Change to DIRECTORY before doing anything.
-d                    Print lots of debugging information.
--debug[=FLAGS]        Print various types of debugging information.
-e, --environment-overrides
                        Environment variables override makefiles.
--eval=STRING           Evaluate STRING as a makefile statement.
-f FILE, --file=FILE, --makefile=FILE
                        Read FILE as a makefile.
-h, --help             Print this message and exit.
-i, --ignore-errors     Ignore errors from recipes.
-I DIRECTORY, --include-dir=DIRECTORY
                        Search DIRECTORY for included makefiles.
-j [N], --jobs[=N]      Allow N jobs at once; infinite jobs with no arg.
-k, --keep-going        Keep going when some targets can't be made.
-l [N], --load-average[=N], --max-load[=N]
                        Don't start multiple jobs unless load is below N.
-L, --check-symlink-times
                        Use the latest mtime between symlinks and target.
-n, --just-print, --dry-run, --recon
                        Don't actually run any recipe; just print them.
-o FILE, --old-file=FILE, --assume-old=FILE
                        Consider FILE to be very old and don't remake it.
-p, --print-data-base    Print make's internal database.
-q, --question          Run no recipe; exit status says if up to date.
-r, --no-builtin-rules   Disable the built-in implicit rules.
-R, --no-builtin-variables
                        Disable the built-in variable settings.
-s, --silent, --quiet    Don't echo recipes.
-S, --no-keep-going, --stop
                        Turns off -k.
-t, --touch             Touch targets instead of remaking them.

```

-v, --version Print the version number of make and exit.
 -w, --print-directory Print the current directory.
 --no-print-directory Turn off -w, even if it was turned on implicitly.
 -W FILE, --what-if=FILE, --new-file=FILE, --assume-new=FILE
 Consider FILE to be infinitely new.
 --warn-undefined-variables Warn when an undefined variable is referenced.

This program built for i386-pc-mingw32

Report bugs to <bug-make@gnu.org>

ChWin32.cpp

C:\MinGW\bin\mingw32-make: invalid option -- c
 C:\MinGW\bin\mingw32-make: invalid option -- Y
 C:\MinGW\bin\mingw32-make: invalid option -- E
 C:\MinGW\bin\mingw32-make: invalid option -- A
 C:\MinGW\bin\mingw32-make: invalid option -- =
 C:\MinGW\bin\mingw32-make: invalid option -- 2
 C:\MinGW\bin\mingw32-make: invalid option -- 0
 C:\MinGW\bin\mingw32-make: invalid option -- 1
 C:\MinGW\bin\mingw32-make: invalid option -- 0
 C:\MinGW\bin\mingw32-make: invalid option -- M
 C:\MinGW\bin\mingw32-make: invalid option -- O
 C:\MinGW\bin\mingw32-make: invalid option -- N
 C:\MinGW\bin\mingw32-make: invalid option -- T
 C:\MinGW\bin\mingw32-make: invalid option -- H
 C:\MinGW\bin\mingw32-make: invalid option -- =
 C:\MinGW\bin\mingw32-make: invalid option -- 9
 C:\MinGW\bin\mingw32-make: invalid option -- A
 C:\MinGW\bin\mingw32-make: invalid option -- Y
 C:\MinGW\bin\mingw32-make: invalid option -- =
 C:\MinGW\bin\mingw32-make: invalid option -- 1
 C:\MinGW\bin\mingw32-make: invalid option -- H
 C:\MinGW\bin\mingw32-make: invalid option -- O
 C:\MinGW\bin\mingw32-make: invalid option -- U
 C:\MinGW\bin\mingw32-make: invalid option -- =
 C:\MinGW\bin\mingw32-make: invalid option -- 1
 C:\MinGW\bin\mingw32-make: invalid option -- 5
 C:\MinGW\bin\mingw32-make: invalid option -- M
 C:\MinGW\bin\mingw32-make: invalid option -- E
 C:\MinGW\bin\mingw32-make: invalid option -- 3
 C:\MinGW\bin\mingw32-make: invalid option -- 2
 C:\MinGW\bin\mingw32-make: invalid option -- g
 C:\MinGW\bin\mingw32-make: invalid option -- 2
 C:\MinGW\bin\mingw32-make: invalid option -- a
 C:\MinGW\bin\mingw32-make: invalid option -- c
 C:\MinGW\bin\mingw32-make: invalid option -- _
 C:\MinGW\bin\mingw32-make: invalid option -- E
 C:\MinGW\bin\mingw32-make: invalid option -- U
 C:\MinGW\bin\mingw32-make: invalid option -- G

C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- g
C:\MinGW\bin\mingw32-make: invalid option -- a
C:\MinGW\bin\mingw32-make: invalid option -- x
Usage: mingw32-make [options] [target] ...

Options:

- b, -m Ignored for compatibility.
- B, --always-make Unconditionally make all targets.
- C DIRECTORY, --directory=DIRECTORY
Change to DIRECTORY before doing anything.
- d Print lots of debugging information.
- debug[=FLAGS] Print various types of debugging information.
- e, --environment-overrides
Environment variables override makefiles.
- eval=STRING Evaluate STRING as a makefile statement.
- f FILE, --file=FILE, --makefile=FILE
Read FILE as a makefile.
- h, --help Print this message and exit.
- i, --ignore-errors Ignore errors from recipes.
- I DIRECTORY, --include-dir=DIRECTORY
Search DIRECTORY for included makefiles.
- j [N], --jobs[=N] Allow N jobs at once; infinite jobs with no arg.
- k, --keep-going Keep going when some targets can't be made.
- l [N], --load-average[=N], --max-load[=N]
Don't start multiple jobs unless load is below N.
- L, --check-symlink-times Use the latest mtime between symlinks and target.
- n, --just-print, --dry-run, --recon
Don't actually run any recipe; just print them.
- o FILE, --old-file=FILE, --assume-old=FILE
Consider FILE to be very old and don't remake it.
- p, --print-data-base Print make's internal database.
- q, --question Run no recipe; exit status says if up to date.
- r, --no-builtin-rules Disable the built-in implicit rules.
- R, --no-builtin-variables Disable the built-in variable settings.
- s, --silent, --quiet Don't echo recipes.
- S, --no-keep-going, --stop
Turns off -k.
- t, --touch Touch targets instead of remaking them.
- v, --version Print the version number of make and exit.
- w, --print-directory Print the current directory.
- no-print-directory Turn off -w, even if it was turned on implicitly.
- W FILE, --what-if=FILE, --new-file=FILE, --assume-new=FILE
Consider FILE to be infinitely new.
- warn-undefined-variables Warn when an undefined variable is referenced.

This program built for i386-pc-mingw32
Report bugs to <bug-make@gnu.org>

CtrlLib.icpp

C:\MinGW\bin\mingw32-make: invalid option -- c
C:\MinGW\bin\mingw32-make: invalid option -- Y
C:\MinGW\bin\mingw32-make: invalid option -- E
C:\MinGW\bin\mingw32-make: invalid option -- A
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- M
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- N
C:\MinGW\bin\mingw32-make: invalid option -- T
C:\MinGW\bin\mingw32-make: invalid option -- H
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 9
C:\MinGW\bin\mingw32-make: invalid option -- A
C:\MinGW\bin\mingw32-make: invalid option -- Y
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- H
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- U
C:\MinGW\bin\mingw32-make: invalid option -- =
C:\MinGW\bin\mingw32-make: invalid option -- 1
C:\MinGW\bin\mingw32-make: invalid option -- 5
C:\MinGW\bin\mingw32-make: invalid option -- M
C:\MinGW\bin\mingw32-make: invalid option -- E
C:\MinGW\bin\mingw32-make: invalid option -- 3
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- g
C:\MinGW\bin\mingw32-make: invalid option -- 2
C:\MinGW\bin\mingw32-make: invalid option -- a
C:\MinGW\bin\mingw32-make: invalid option -- c
C:\MinGW\bin\mingw32-make: invalid option -- _
C:\MinGW\bin\mingw32-make: invalid option -- E
C:\MinGW\bin\mingw32-make: invalid option -- U
C:\MinGW\bin\mingw32-make: invalid option -- G
C:\MinGW\bin\mingw32-make: invalid option -- O
C:\MinGW\bin\mingw32-make: invalid option -- 0
C:\MinGW\bin\mingw32-make: invalid option -- g
C:\MinGW\bin\mingw32-make: invalid option -- a
C:\MinGW\bin\mingw32-make: invalid option -- x
Usage: mingw32-make [options] [target] ...

Options:

- b, -m Ignored for compatibility.
- B, --always-make Unconditionally make all targets.

-C DIRECTORY, --directory=DIRECTORY
 Change to DIRECTORY before doing anything.
 -d Print lots of debugging information.
 --debug[=FLAGS] Print various types of debugging information.
 -e, --environment-overrides
 Environment variables override makefiles.
 --eval=STRING Evaluate STRING as a makefile statement.
 -f FILE, --file=FILE, --makefile=FILE
 Read FILE as a makefile.
 -h, --help Print this message and exit.
 -i, --ignore-errors Ignore errors from recipes.
 -I DIRECTORY, --include-dir=DIRECTORY
 Search DIRECTORY for included makefiles.
 -j [N], --jobs[=N] Allow N jobs at once; infinite jobs with no arg.
 -k, --keep-going Keep going when some targets can't be made.
 -l [N], --load-average[=N], --max-load[=N]
 Don't start multiple jobs unless load is below N.
 -L, --check-symlink-times Use the latest mtime between symlinks and target.
 -n, --just-print, --dry-run, --recon
 Don't actually run any recipe; just print them.
 -o FILE, --old-file=FILE, --assume-old=FILE
 Consider FILE to be very old and don't remake it.
 -p, --print-data-base Print make's internal database.
 -q, --question Run no recipe; exit status says if up to date.
 -r, --no-builtin-rules Disable the built-in implicit rules.
 -R, --no-builtin-variables Disable the built-in variable settings.
 -s, --silent, --quiet Don't echo recipes.
 -S, --no-keep-going, --stop
 Turns off -k.
 -t, --touch Touch targets instead of remaking them.
 -v, --version Print the version number of make and exit.
 -w, --print-directory Print the current directory.
 --no-print-directory Turn off -w, even if it was turned on implicitly.
 -W FILE, --what-if=FILE, --new-file=FILE, --assume-new=FILE
 Consider FILE to be infinitely new.
 --warn-undefined-variables Warn when an undefined variable is referenced.

This program built for i386-pc-mingw32

Report bugs to <bug-make@gnu.org>

CtrlLib: 53 file(s) built in (0:00.30), 5 msec / file, duration = 571 msec

There were errors. (0:00.68)