
Subject: Re: [BUG?] X11 (at least OSX) Menus displayed under TopWindow,
owner=RootWindow

Posted by [fudadmin](#) on Fri, 28 Jan 2011 13:03:43 GMT

[View Forum Message](#) <> [Reply to Message](#)

I think I have the remedy.

in CtrlKbd.cpp,
if I comment the line

topwindow->SetWndForeground(); // cxl 2007-4-27

the menus are displayed properly. Any side effects from your point of view?

like this:

```
bool Ctrl::SetFocus0(bool activate)
{
    GuiLock __;
    if(IsUsrLog())
        UsrLogT(6, String().Cat() << "SETFOCUS " << Desc(this));
    LLOG("Ctrl::SetFocus " << Desc(this));
    LLOG("focusCtrlWnd " << UPP::Name(focusCtrlWnd));
    LLOG("Ctrl::SetFocus0 -> deferredSetFocus = NULL; was: " << UPP::Name(deferredSetFocus));
    deferredSetFocus = NULL;
    if(focusCtrl == this) return true;
    if(!IsOpen() || !IsEnabled() || !IsVisible()) return false;
    Ptr<Ctrl> pfocusCtrl = focusCtrl;
    Ptr<Ctrl> topwindow = GetTopWindow();
    Ptr<Ctrl> topctrl = GetTopCtrl();
    Ptr<Ctrl> _this = this;
    if(!topwindow) topwindow = topctrl;
    LLOG("SetFocus -> SetWndFocus: topwindow = " << UPP::Name(topwindow) << ", focusCtrlWnd
= " << UPP::Name(focusCtrlWnd));
    if(!topwindow->HasWndFocus() && !topwindow->SetWndFocus()) return false;// cxl 31.1.2004
    // topwindow->SetWndForeground(); // cxl 2007-4-27
    LLOG("SetFocus -> focusCtrl = this: " << FormatIntHex(this) << ", _this = " <<
FormatIntHex(~_this) << ", " << UPP::Name(_this));
    focusCtrl = _this;
    focusCtrlWnd = topwindow;
    DoKillFocus(pfocusCtrl, _this);
    LLOG("SetFocus 2 - after DoKillFocus");
    DoDeactivate(pfocusCtrl, _this);
    DoSetFocus(pfocusCtrl, _this, activate);
    if(topwindow)
        lastActiveWnd = topwindow;
    return true;
}
```
