
Subject: Re: Proposed change to U++ to allow owning children.

Posted by [Lance](#) on Fri, 18 Mar 2011 23:02:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thank you very much! I have no doubt with U++'s speed. That's one big aspect why it attracts me.

Very informative.

Since you are here, how do you like my way of revised Ctrl::Ctrl implementation?

```
Ctrl::Ctrl() {
    GuiLock __;
    LLOG("Ctrl::Ctrl");

    // a smarter way to implement this function
    // as we can see, most member variable to initialized
    // to 0, we can save a couple of cpu cycles by simply
    // zero out the part of object that are of POD type

    // Note Non-POD member variable frame, info, pos has been move to
    // follow POD members, with pos being the first non-pod member var.
    typedef int32 unit; // 4 should be deduced for flexibility
    unsigned size=((char*)&this->pos -(char*)this)/sizeof(unit);
    for(unsigned i=0; i<size; ++i)
        reinterpret_cast<unit*>(this)[i]=0;

    //destroying = false;
    //owned = false;
    //parent = prev = next = firstchild = lastchild = NULL;
    //top = NULL;
    //exitcode = 0;
    frame.Add().frame = &NullFrame();
    enabled = visible = wantfocus = initfocus = true;
    editable = true;
    // GLX = false;
#ifdef PLATFORM_WIN32
    //activex = false;
    //isdhctrl = false;
#endif
    backpaint = IsCompositedGui() ? FULLBACKPAINT : TRANSPARENTBACKPAINT;
    //inframe = false;
    //ignoremouse = transparent = false;
    //caretcx = caretcy = caretX = caretY = 0;
    //SetRect(Rect(0, 0, 0, 0));
    //inloop = popup = isopen = false;
    //modify = false;
```

```
//unicode = false;  
//popupgrab = false;  
//fullrefresh = false;  
//akv = false;  
//hasdhctrl = false;  
}
```
