

---

Subject: Re: Database with several windows  
Posted by [BioBytes](#) on Sun, 26 Jun 2011 06:49:08 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

Try to use Sqlld identifiers as global variables in your applications. It makes things easier to manage fields from different tables in the same application. For example, I use :

```
TABLE (NATIONS)
INT(IDNATION)PRIMARY_KEY AUTO_INCREMENT
STRING_(NATION,200)
STRING_(STATUS,50)
BLOB(FLAG)
END_TABLE
```

```
TABLE (UNITS)
INT(ID)PRIMARY_KEY AUTO_INCREMENT
INT (IDUNIT)
STRING_(UNITNAME,200)
BLOB(UNITPICTURE)
END_TABLE
```

```
TABLE (MAPS)
INT(IDMAP)PRIMARY_KEY AUTO_INCREMENT
INT(MAPNUMBER)
INT(MODULEOWNER)
STRING_(DESCRIPTION,200)
BLOB(MAPPICTURE)
END_TABLE
```

```
TABLE (MODULES)
INT(IDMODULE)PRIMARY_KEY AUTO_INCREMENT
STRING_(MODULENAME,200)
STRING_(EDITOR,200)
END_TABLE
```

and the Sqlld:

```
Sqlld TBLMAPS("MAPS"),TBLNATIONS("NATIONS"),TBLUNITS("UNITS"),TBLMODULES(
"MODULES"),IDNATION("IDNATION"),
  ID("ID"),IDMOD("IDMODULE"),IDUNIT("IDUNIT"),UNIT("UNITNAME
"),IDM("IDMAP"),NUMBER("MAPNUMBER"),
  MAPIMG("MAPPICTURE"),UNITIMAGE("UNITPICTURE"),OWNER("MODULEOWNER
"),DESC("DESCRIPTION"),FLAG("FLAG"),
  STATUT("STATUS"),NAME("NATION"),MODULE("MODULENAME"),EDITORMOD(
"EDITOR"),ALL("");
```

Sqlite3Session ASLDBSession;

Hoping this could be helpful

Regards

Biobytes

---