
Subject: Re: Editing TreeCtrl Node Value

Posted by [mirek](#) on Fri, 25 Nov 2011 12:49:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

kropniczki wrote on Thu, 24 November 2011 19:50I improvised with the following code:

.h:

```
class App : public TopWindow {
public:
    typedef App CLASSNAME;
    App();

private:
    struct TreeEdit : public EditString {
        Callback WhenLostFocus;
        TreeEdit() {}
        virtual void LostFocus() { WhenLostFocus(); }
    };

    bool        isedit;
    int         nodeid;
    TreeCtrl::Node editnode, node;
    TreeEdit    edit;
    TreeCtrl    tree;

    void EditBranch();
    void CloseEdit();
};
```

.cpp:

```
App::App() : isedit(false), nodeid(-1) {
    Add(tree.SizePos());
    /*
    ...
    Populate TreeCtrl here
    ...
    */
    tree.WhenLeftClick = THISBACK(EditBranch);
    editnode.SetCtrl(edit);
    edit.WhenEnter = THISBACK(CloseEdit);
    edit.WhenLostFocus = THISBACK(CloseEdit);
}

void App::EditBranch()
{
```

```

if(isedit) {
    CloseEdit();
    return;
}
if(nodeid != tree.GetCursor()) {
    nodeid = tree.GetCursor();
    return;
}
isedit = true;
node = tree.GetNode(nodeid);
editnode.ctrl->SetData(node.value);
editnode.image = node.image;
groups.SetNode(nodeid, editnode);
editnode.ctrl->Show();
}

```

```

void App::CloseEdit()
{
    node.value = editnode.ctrl->GetData();
    tree.SetNode(nodeid, node);
    tree.SelectOne(nodeid);
    editnode.ctrl->Hide();
    isedit = false;
}

```

It works in a way, but I guess there must be an easier way of accomplishing this.

thanks for any help.

Unfortunately, this mode of edit is not directly supported (yet?).
