
Subject: Re: DragAndDrop FILES does not work under LINUX

Posted by [Didier](#) on Tue, 27 Dec 2011 20:49:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

I tested with gnome and it also works fine,

Seems to be a KDE specific problem

But looking at the logs in DEBUG mode

In GNOME:

```
##### PasteClip =
```

```
Target action 1
```

```
Sending status/finished to 23115959 accepted: true
```

```
DropStatus Client Message XdndPosition
```

```
Client Message 83890900 XdndPosition, src: 23115959
```

```
XdndPosition [757, 350], action XdndActionCopy
```

```
Source action 1
```

```
##### PasteClip =
```

```
Target action 1
```

```
Sending status/finished to 23115959 accepted: true
```

```
DropStatus Client Message XdndPosition
```

```
Client Message 83890900 XdndPosition, src: 23115959
```

```
XdndPosition [759, 352], action XdndActionCopy
```

```
Source action 1
```

```
##### PasteClip =
```

```
Target action 1
```

```
Sending status/finished to 23115959 accepted: true
```

```
DropStatus Client Message XdndPosition
```

```
Client Message 83890900 XdndPosition, src: 23115959
```

```
XdndPosition [760, 353], action XdndActionCopy
```

```
Source action 1
```

```
##### PasteClip =
```

```
Target action 1
```

```
Sending status/finished to 23115959 accepted: true
```

```
##### PasteClip =
```

```
##### PasteClip =
```

```
##### PasteClip =
```

```
##### PasteClip =
```

```
##### PasteClip =
```

```
DropStatus Client Message XdndDrop
```

```
Client Message 83890900 XdndDrop, src: 23115959
```

```
XdndDrop to 10VMLineEdit : 0xbf82c308(parent 16WithTabDocLayoutIN3Upp10ParentCtrlEE)
```

```
Source action 1
```

```
##### PasteClip =
```

```
Target action 1
```

```
Sending status/finished to 23115959 accepted: true
```

DropStatus Client Message WM_PROTOCOLS
DropStatus Client Message WM_PROTOCOLS
DropStatus Client Message WM_PROTOCOLS

In KDE

DropStatus Client Message XdndPosition
Client Message 85985289 XdndPosition, src: 81788964
XdndPosition [1023, 365], action XdndActionMove
Source action 2
PasteClip =
Target action 2
Sending status/finished to 81788964 accepted: true
PasteClip =
PasteClip =
DropStatus Client Message XdndPosition
Client Message 85985289 XdndPosition, src: 81788964
XdndPosition [1023, 365], action XdndActionMove
Source action 2
PasteClip =
Target action 2
Sending status/finished to 81788964 accepted: true
PasteClip =
PasteClip =
PasteClip =
PasteClip =
DropStatus Client Message XdndPosition
Client Message 85985289 XdndPosition, src: 81788964
XdndPosition [1023, 365], action XdndActionMove
Source action 2
PasteClip =
Target action 2
Sending status/finished to 81788964 accepted: true
PasteClip =
PasteClip =
PasteClip =
DropStatus Client Message XdndDrop
Client Message 85985289 XdndDrop, src: 81788964
XdndDrop to 10VMLineEdit : 0xbfb1fde8(parent 16WithTabDocLayoutIN3Upp10ParentCtrlEE)
Source action 2
PasteClip =
Target action 2
Sending status/finished to 81788964 accepted: true
DropStatus Client Message WM_PROTOCOLS
DropStatus Client Message WM_PROTOCOLS
DropStatus Client Message WM_PROTOCOLS

The target action differs: 1 in GNOME and 2 in KDE

You are certainly right saying it's a protocol problem.

Where is all this protocol parsing done, i can try and take a look at what can be done ?