
Subject: An OpenGL ctrl for Linux / X11
Posted by [cyrion](#) on Fri, 02 Jun 2006 16:40:19 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

I have just finished (the first version of) an opengl ctrl for X11.
It works well but I had to make modifications to U++ core, and I would like to know if there is a
best way to proceed.

The modifications I have made are:

1/ in CtrlCore.h, class Ctrl :

* I put the static `ArrayMap<> Xwindow()` in protected section.
I had to do so because the `Create()` method does not allow to use another X visual than the top
window one. So I had to put my new X (sub)window "by hand" into the static `ArrayMap` of
windows.

* I added a 'bool UseGLXVisual' (in protected section), defaulting to false except in my new Ctrl.

2/ in X11Wnd.h

* in `Ctrl::DoPaint()`, I 'return' without creating a GC if `UseGLXVisual` is true (just before
`XCreateGC`).
I had to do so to prevent the `Ctrl::Draw()` method to be called with a GC context that is not
compatible with my X window.

Finally, all seems to work fine : resizing, moving, hide/show, multiple gl ctrls, etc...

I hope that the source code will be more comprehensible than my english.

Btw, many many thanks for this wonderful library !

Damien
(Linux 2.6, debian, Xorg, U++ 605)

File Attachments

1) [openglctrl.tgz](#), downloaded 1881 times
