
Subject: Witz and Skylark weird behaviour (possibly a bug)

Posted by [Peter](#) on Fri, 21 Dec 2012 14:12:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello.

Let's start with the code:

main.cpp:

```
#include <Skylark/Skylark.h>

using namespace Upp;

SKYLARK(HomePage, "")
{
    ValueMap Ing;
    Ing.Add(LNG_(P,L,P,L), "Polish");
    Ing.Add(LNG_(E,N,U,S), "English");
    http("LNG_LIST", Ing).RenderResult("Skylark_Bug/page");
}

SKYLARK(CatchAll, "***")
{
    http.Redirect(HomePage);
}

struct MyApp : SkylarkApp {

    MyApp() {
        #ifdef _DEBUG
        prefork = 0;
        use_caching = false;
        #endif
    }
};

CONSOLE_APP_MAIN
{
    #ifdef _DEBUG
    StdLogSetup(LOG_FILE|LOG_COUT);
    Ini::skylark_log = true;
    #endif
    MyApp().Run();
}
```

page.witz:

```
<html>
<body>

<form action=$ACTION method="post" accept-charset="utf-8" enctype="multipart/form-data">
$post_identity()
<select name="language">
$for(i in LNG_LIST)
<option value="">$i</option>
$/
</select>
</form>

</body>
</html>
```

When I compile the above code, run the application and go to its root page, I should see a menu from which I can choose one of two languages. What I see instead is some random ID string as both menu options. However, when I refresh the page, it suddenly displays menu contents correctly (see the attached files wrong.html and correct.html for reference).

If I change `<option value="">` to `<option value="$i._key">` and try to display the page for the first time, the whole application crashes due to a segmentation fault.

I investigated the problem and I know it's caused by
"\$post_identity()" in page.witz (that's where the random ID comes from).

Why are the page contents wrong the first time it's displayed (a value from a hidden field overrides both valid values from ValueMap) and why are the correct values displayed after reloading the page? Finally, why does a reference to `i._key` in page.witz cause a crash? I imagine why it can happen - I'm trying to retrieve the key of a random ID which is not an element of my ValueMap, but is this the expected behaviour? Shouldn't it evaluate to null, empty string etc. instead of causing a segmentation fault?

Is it a problem with Witz or Skylark or both?

Best regards

Peter

File Attachments

- 1) [wrong.html](#), downloaded 356 times
 - 2) [correct.html](#), downloaded 351 times
-