
Subject: Re: Upp package binding for LLVM/Clang library (libclang)

Posted by [Sender Ghost](#) on Sun, 26 May 2013 19:04:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello, Didier.

Didier wrote on Sun, 26 May 2013 20:11 Obviously my BM file is incomplete/wrong but what is wrong ??

Usually, I use following command to get default include directories for GCC compiler:

```
gcc -v -fsyntax-only -x c++ test.c
```

where test.c is path to file with following contents:

```
#include <stdio.h>
```

```
int main() {  
    return 0;  
}
```

The excerpt of output might look like follows:

#include "..." search starts here:

#include <...> search starts here:

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\include\c++
```

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\include\c++\mingw32
```

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\include\c++\backward
```

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\include
```

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\..\..\..\include
```

```
c:\mingw\bin\..\lib\gcc\mingw32\4.7.1\include-fixed
```

End of search list. Then the default include directories (for concrete compiler version) are:

```
c:\mingw\lib\gcc\mingw32\4.7.1\include\c++
```

```
c:\mingw\lib\gcc\mingw32\4.7.1\include\c++\mingw32
```

```
c:\mingw\lib\gcc\mingw32\4.7.1\include\c++\backward
```

```
c:\mingw\lib\gcc\mingw32\4.7.1\include
```

```
c:\mingw\include
```

```
c:\mingw\lib\gcc\mingw32\4.7.1\include-fixed
```
