

I propose to make this changes in DateTimeCtrl.cpp & DateTimeCtrl.h

DateTimeCtrl.h have 3 changes:

1. After line 212 add line

Callback3 <Date , Color&, Color& > WhenPaintDay;
result:

public:

Calendar();

Callback1<Time &> WhenTime;

Callback3 <Date , Color&, Color& > WhenPaintDay; // <== Inserted line

static const Style& StyleDefault();

void Reset();

2. After line 491 add line

Callback3 <Date , Color&, Color& > WhenPaintDay;

3. After line 501 add line

cc.calendar.WhenPaintDay = Proxy(WhenPaintDay);

result of items 2 & 3 will be:

public:

typedef DateTimeCtrl CLASSNAME;

Callback3 <Date , Color&, Color& > WhenPaintDay; // <== Inserted line

DateTimeCtrl(int m) : cc(m) {

drop.AddTo(*this);

drop.AddButton().Main() <== THISBACK(OnDrop);

drop.NoDisplay();

drop.SetStyle(drop.StyleFrame());

drop.GetButton(0).SetMonolImage(Grayscale(CtrlImg::DA()));

cc.calendar <== THISBACK(OnCalendarChoice);

cc.clock <== THISBACK(OnClockChoice);

cc.WhenPopDown = THISBACK(OnClose);

cc.calendar.WhenSelect = Proxy(WhenSelect);

cc.calendar.WhenPaintDay = Proxy(WhenPaintDay); // <== Inserted line

```

}
virtual void GotFocus() { T::GotFocus(); drop.RefreshFrame(); }
virtual void LostFocus() { T::LostFocus(); drop.RefreshFrame(); }
virtual Size GetMinSize() const { return drop.GetMinSize(); }

```

DateTimeCtrl.cpp have 1 changes:

1. After line 530 add lines:

```

if (!WhenPaintDay.Empty()){
    WhenPaintDay(Date(y,m,d),fg,bg);
}

```

result code:

```

if(d == today.day && m == today.month && y == today.year)
{
    fg = st.fgtoday;
    bg = st.bgtoday;
    fnt.Bold();
    special = true;

    curday.x = j;
    curday.y = i;
}
if(d == sel.day && m == sel.month && y == sel.year)
{
    fg = st.fgselect;
    bg = st.bgselect;
    fnt.Bold();
    special = true;

    prevday.x = j;
    prevday.y = i;
}
if (!WhenPaintDay.Empty()){           // <== Inserted line
    WhenPaintDay(Date(y,m,d),fg,bg); // <== Inserted line
}                                     // <== Inserted line

}
else
{
    fg = st.outofmonth;
    sd = d > 0 ? -d : d;
    Day(j, i) = sd;
}

```

```
}
```

In attachment these 2 files based on 6113svn

PS

Please include my addition into standard code.

File Attachments

1) [DateTimeCtrl-new.tar.gz](#), downloaded 366 times
