Subject: 6715 nightly build
Posted by mtdew3q on Sat, 04 Jan 2014 17:50:12 GMT
View Forum Message <> Reply to Message

Hi-

I received this message on building gui ctrlib app with this line of code. I just checked to see that it would build something before getting started.

I will try a couple of nights ago in a few minutes and see how it goes.

```
#include <CtrlLib/CtrlLib.h>

using namespace Upp;

GUI_APP_MAIN
{
  PromptOK("Hello world");
}
```

I think ctrlib was named .icpp so I changed it to .cpp also. I am going to try another build out. THANKS. ERRORS below. I am using windows with gcc mingw 32 bit.

```
----- Core ( GUI SSE2 GCC32 DEBUG DEBUG_FULL BLITZ WIN32 ) (6 / 9)
BLITZ: Cpu.cpp Mt.cpp sheap.cpp String.cpp WString.cpp StrUtil.cpp Bom.cpp Path.cpp
NetNode.cpp App.cpp Stream.cpp BlockStream.cpp FilterStre
 am.cpp Log.cpp Debug.cpp Ini.cpp Util.cpp mathutil.cpp Random.cpp LocalProcess.cpp
Vcont.cpp Hash.cpp Callback.cpp TimeDate.cpp Value.cpp Val
 ueUtil.cpp Format.cpp Convert.cpp Color.cpp Gtypes.cpp t.cpp Lang.cpp LangInfo.cpp
parser.cpp XML.cpp Xmlize.cpp JSON.cpp Uuid.cpp Ptr.cpp z.
 cpp Topic.cpp CoWork.cpp MD5.cpp SHA1.cpp InetUtil.cpp Socket.cpp Http.cpp WebSocket.cpp
Dli.cpp Win32Util.cpp
OL_Set.cpp
In file included from  C:/upp/out/MyApps/Core/MINGW.Debug.Debug_Full.Gui.Sse2\$blit
z.cpp:453:0:
C:\upp\uppsrc\Core\Socket.cpp: In function 'int Upp::sGetAddrInfo(const char*, const char*, int,
addrinfo**)':
C:\upp\uppsrc\Core\Socket.cpp:45:47: error: 'getaddrinfo' was not declared in this scope
  return getaddrinfo(host, port, &hints, result);
                                           ^
C:\upp\uppsrc\Core\Socket.cpp: In static member function 'static DWORD
Upp::IpAddrInfo::Thread(void*)':
C:\upp\uppsrc\Core\Socket.cpp:67:24: error: 'freeaddrinfo' was not declared in this scope
    freeaddrinfo(result);
                 ^
```

```
C:\upp\uppsrc\Core\Socket.cpp: In member function 'void Upp::IpAddrInfo::Clear()':
C:\upp\uppsrc\Core\Socket.cpp:151:28: error: 'freeaddrinfo' was not declared in this scope
    freeaddrinfo(entry->addr);
                        ^
heaputil.cpp
RichText: 22 file(s) built in (0:07.06), 321 msecs / file, duration = 13572 msecs, parallelization
100%
lheap.cpp
heap.cpp
heapdbg.cpp
CharSet.cpp
Core: 56 file(s) built in (0:09.71), 173 msecs / file, duration = 16162 msecs, parallelization 86%

There were errors. (1:07.90)
```