
Subject: Re: mouse wheel, skipping `}}"` chars
Posted by [mirek](#) on Mon, 22 Dec 2014 16:49:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

smxxms wrote on Wed, 10 December 2014 05:54 Maybe i am not aware of these in ide,
but i find them quite usefull - especially with so little piece of code:

```
>>+=-----  
mousewheel, numLinesToScroll read from system:  
at Assist.cpp void AssistEditor::MouseWheel(Point p, int zdelta, dword keyflags)  
int slines;  
SystemParametersInfo(SPI_GETWHEELSCROLLLINES, 0, &slines, 0);  
...  
CodeEditor::MouseWheel(p, zdelta*slines, keyflags);
```

```
>>+=-----  
when same char }}" ahead_written - it's jumped over:  
if((code=='')||code=='||code=='}'||code=='"') &&  
code==GetChar(GetCursor()))SetCursor(GetCursor()+1);  
at CodeEditor.cpp: if(code >= 32 && code < 128 && count == 1) {
```

This is from sources v7936

smx

I have fixed the first issue (but correctly - your code is not platform independent). It is in trunk now.

I am not sure whether I like the second issue. Is there any mainstream editor that provides this behaviour?

Mirek
