
Subject: HttpRequest : Add custom authentication capability

Posted by [omari](#) on Fri, 01 Apr 2016 16:26:30 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

i am trying to use NTLM authentication with HttpRequest,

for NTLM, i note the following particularity:

- Use 3 "GET" request.
- Keep connection alive between at least the last two requests.
- Use DES encryption.

After analysis of the used authentication mechanism in HttpRequest, I propose the following patch:

- 1 - remove the member variable "force_digest" et "digest"
- 2 - add a new member variable String "authenticate_header"
- 3 - in the void HttpRequest::StartRequest(), replace :

```
if(!IsNull(digest))
    data << "Authorization: Digest " << digest << "\r\n";
else
if(!force_digest && (!IsNull(username) || !IsNull(password)))
    data << "Authorization: Basic " << Base64Encode(username + ":" + password) << "\r\n";
```

by

```
data << authenticate_header;
```

- 4 - change 401 error management, in void HttpRequest::Finish(), replace :

```
if(status_code == 401 && !IsNull(username)) {
    String authenticate = header["www-authenticate"];
    if(authenticate.GetCount() && redirect_count++ < max_redirects) {
        LLOG("HTTP auth digest");
        Digest(CalculateDigest(authenticate));
        Start();
        return;
    }
}
```

by

```

if(status_code == 401) {

String authenticate = header["www-authenticate"];
if(authenticate.GetCount() && redirect_count++ < max_redirects) {
    if(!IsNull(username) || !IsNull(password)) {

        if(authenticate.StartsWith("Basic"))
        {
            authenticate_header = "Authorization: Basic " + Base64Encode(username + ":" + password)+ "\r\n";
        }
        else
        if(authenticate.StartsWith("Digest"))
        {
            LLOG("HTTP auth digest");
            authenticate_header = "Authorization: Digest " + CalculateDigest(authenticate) + "\r\n";
        }
        else
        {
            WhenAuthentication(*this);
        }
    }
    else {
        WhenAuthentication(*this);
    }
}

if(keep_alive)
    StartRequest();
else
    Start();

return;
}
}

```

5 - WhenAuthentication is declared as:

```
Callback1<HttpRequest&> WhenAuthentication;
```

6 - Add a method void ForceBasic(String user, String pw)

```
void ForceBasic(String user, String pw) {authenticate_header << "Authorization: Basic " << Base64Encode(user + ":" + pw) << "\r\n";}
```

with this patch, a custom Authentication function can be added :

```
void Autenticate(HttpServletRequest& http)
{
    String www_authenticate = http.GetHeader("www-authenticate");
    if(!www_authenticate.StartsWith("NTLM"))
    {
        return;
    }
    //...
}
...
HttpRequest r;
r.WhenAuthentication = callback(Autenticate);
```
