

---

Subject: Re: Problem with FreeBSD

Posted by [Sender Ghost](#) on Wed, 04 Jan 2017 08:12:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

amrein wrote on Tue, 03 January 2017 12:40 You still need to run 'make prepare -C uppsrc' first  
This is different issue, which you probably encountered with running many threads, while no  
directories created in prepare step, but some file was built first.

I guess, possible to fix this issue with addition of dependencies to prepare rule on directories to  
create. For example, based on uppsrc/umk:

Some example

```
prepare: \  
$(OutDir_umk) \  
$(OutDir_ide_Builders) \  
$(OutDir_ide_Core) \  
$(OutDir_ide_Android) \  
$(OutDir_ide_Java) \  
$(OutDir_Esc) \  
$(OutDir_plugin_bz2) \  
$(OutDir_Core) \  
$(OutDir_plugin_pcre)
```

```
$(OutDir_umk):  
mkdir -p $(OutDir_umk)
```

```
$(OutDir_ide_Builders):  
mkdir -p $(OutDir_ide_Builders)
```

```
$(OutDir_ide_Core):  
mkdir -p $(OutDir_ide_Core)
```

```
$(OutDir_ide_Android):  
mkdir -p $(OutDir_ide_Android)
```

```
$(OutDir_ide_Java):  
mkdir -p $(OutDir_ide_Java)
```

```
$(OutDir_Esc):  
mkdir -p $(OutDir_Esc)
```

```
$(OutDir_plugin_bz2):  
mkdir -p $(OutDir_plugin_bz2)
```

```
$(OutDir_Core):  
mkdir -p $(OutDir_Core)
```

```
$(OutDir_plugin_pcre):  
mkdir -p $(OutDir_plugin_pcre)
```

I attached a patch (based on 10617 revision of uppsrc/ide/Builders/Build.cpp file), which adds this for exported Makefile.

How to apply the patch, just in case:

```
$ cd path/to/upp
```

```
$ patch -B " < uppsrc_prepare_r10617.diff
```

You may need to rebuild uppsrc/umk or uppsrc/ide and do your own export/build to test this patch.

## File Attachments

---

1) [uppsrc\\_prepare\\_r10617.diff](#), downloaded 360 times

---