
Subject: SKYLARK js: I offer that we expanded the UxGet function a little with parameter callback

Posted by [sergeynikitin](#) on Fri, 27 Jan 2017 04:09:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

I offer that we expanded the UxGet function a little with parameter callback function.

It can be, by Uxget call from javascript. For example for processing of the conditional display-hiding and layout arrangement when it is necessary to cause function right after loading of AJAX of result.

example of use (in html page):

```
<script type="text/javascript">
```

```
var hiding = false;
```

```
function update_expand_hiding_status() {
```

```
    // some updates ... of css and div attributes
```

```
}
```

```
function maintable_update(){
```

```
    if (enable_update){
```

```
        //UxGet($MainReportTableUpdate);
```

```
        UxGet($MainTableUpdate,update_expand_hiding_status);
```

```
    }
```

```
};
```

```
</script>
```

modification of skylark.js::

```
function UxGet(request,callback) // <=====Add parameter as callback function
```

```
{
```

```
    var xmlhttp = AjaxRequest();
```

```
    xmlhttp.onreadystatechange = function() {
```

```
        if(xmlhttp.readyState == 4 && xmlhttp.status == 200) {
```

```
            ProcessAjaxResult(xmlhttp.responseText.split('\n'));
```

```
            if (callback) { // <===== if parameter callback is passed,
```

```
                callback();// <===== call parameter function.
```

```
            } // <=====
```

```
        }
```

```
    }
```

```
    xmlhttp.open("GET", request, true);
```

```
    xmlhttp.send();
```

```
}
```
