Subject: SKYLARK js: I offer that we expanded the UxGet function a little with parameter callback
Posted by sergeynikitin on Fri, 27 Jan 2017 04:09:04 GMT
View Forum Message <> Reply to Message

I offer that we expanded the UxGet function a little with parameter callback function.

It can be, by Uxget call from javascript. For example for processing of the conditional display-hiding and layout arrangement when it is necessary to cause function right after loading of AJAX of result.

example of use (in html page):

```
<script  type="text/javascript">
 var hiding = false;
 function update_expand_hiding_status() {
  // some updates ... of css and div attributes
 }

 function maintable_update(){
  if (enable_update){
   //UxGet($MainReportTableUpdate);
   UxGet($MainTableUpdate,update_expand_hiding_status);
  }
 };

</script>
```

modification of skylark.js::

```
function UxGet(request,callback) // <===========Add parameter as callback function
{
 var xmlhttp = AjaxRequest();
 xmlhttp.onreadystatechange = function() {
  if(xmlhttp.readyState == 4 && xmlhttp.status == 200) {
   ProcessAjaxResult(xmlhttp.responseText.split('\1'));
   if (callback) {    // <=========== if parameter callback is passed,
    callback();// <=========== call parameter function.
    }                // <===========
  }
 }
 xmlhttp.open("GET", request, true);
 xmlhttp.send();
}
```