
Subject: FormatBytes function

Posted by [Oblivion](#) on Thu, 20 Apr 2017 23:18:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

FormatBytes() is a very simple and useful formatter which can be used for displaying file/transfer size etc.

```
String FormatBytes(int64 bytes, bool kilo = false)
{
    const char* base1000[] = { "B", "KB", "MB", "GB", "TB", "PB", "EB", "YB", "ZB" };
    const char* base1024[] = { "B", "KiB", "MiB", "GiB", "TiB", "PiB", "EiB", "YiB", "ZiB" };

    int base = kilo ? 1000 : 1024;
    int exponent = floor(log2(bytes) / log2(base));

    return bytes < base
        ? FormatInt64(bytes) << " " << (kilo ? base1000[0] : base1024[0])
        : Format("%.1f %s", bytes / pow(base, exponent), kilo ? base1000[exponent] :
base1024[exponent]);
}
```

Example output:

----- Base:1024(kibi)--Base:1000(kilo)

```
1) 1023 (bytes) -> 1023 B 1.0 KB
2) 2046 (bytes) -> 2.0 KiB 2.0 KB
3) 3069 (bytes) -> 3.0 KiB 3.1 KB
4) 4092 (bytes) -> 4.0 KiB 4.1 KB
5) 5115 (bytes) -> 5.0 KiB 5.1 KB
6) 6138 (bytes) -> 6.0 KiB 6.1 KB
7) 7161 (bytes) -> 7.0 KiB 7.2 KB
8) 8184 (bytes) -> 8.0 KiB 8.2 KB
9) 9207 (bytes) -> 9.0 KiB 9.2 KB
```

Since it has a simple and strict format (number/SPACE/unit) it can be parsed if needed.
Is it possible to add this, or something similar to this, to U++ formatters?
It is very handy if you work with files and data transfers.

Regards,

