
Subject: Re: [SQLITE] Search accents insensitive

Posted by [jibe](#) on Fri, 30 Jun 2017 09:12:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

Ooops !

```
extern "C" {  
    void Sqlite3NoAccents(sqlite3_context *context, int argc, sqlite3_value **argv) {  
        String str = RemoveAccents((const char*)sqlite3_value_text(argv[0]));  
        sqlite3_result_text(context, ~str, str.GetCount(), SQLITE_TRANSIENT);  
        return;  
    }  
}
```

```
void (*pSqlite3NoAccents)(sqlite3_context *, int, sqlite3_value **);  
Sqlite3Session sqlite3;  
::sqlite3* sqlite3db = (::sqlite3*)(Sqlite3Session::sqlite3*)sqlite3;  
sqlite3_create_function(sqlite3db, "NoAccents", 1, SQLITE_ANY, 0, pSqlite3NoAccents, 0, 0);
```

is surely a lot better ! The compiler accepts it very well, but stays a
/home/joseph/uppMyApps/Owl/book.cpp (2891): error: 'NoAccents' was not declared in this scope

Seems normal that the compiler complains, but I don't know how to declare it...

The sqlite3_create_function is called in main(), when I use the "NoAccents" (Sqlite3NoAccents) in
a dialog box...

```
w = (Like ((SqlId)NoAccents((SqlId)("TITLE")), "% " + AsString(~str) + "%"));  
book.Query(w);  
(book is a SqlArray in the dialog's layer)
```