
Subject: Re: [PROPOSAL] Redesigned Assembly Setup Dialog

Posted by [Sender Ghost](#) on Sat, 16 Jun 2018 10:10:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

Klugier wrote on Fri, 15 June 2018 22:42 This diff format is useless when you operate with upp trunk.

I think, this is not true and probably may depend from used tools.

For example, attached patch from previous message applies with using `svn patch` command:

```
% fetch -qo uppsrc_ide.diff "https://www.ultimatepp.org/forums/index.php?t=getfile&id=5620"
```

```
% sha256 uppsrc_ide.diff
```

```
SHA256 (uppsrc_ide.diff) =
```

```
6a4fab696fbf2c70b01051a381b93d1b3af5ed172dca56820bb50887c7ff6bda
```

```
% svn --version | head -1
```

```
svn, version 1.10.0 (r1827917)
```

```
% svn co -r 11996 svn://www.ultimatepp.org/upp/trunk upp
```

```
<...>
```

```
% cd upp
```

```
% svn patch ../uppsrc_ide.diff
```

```
U      uppsrc/ide/BaseDlg.cpp
```

```
U      uppsrc/ide/MethodsCtrls.cpp
```

```
U      uppsrc/ide/MethodsCtrls.h
```

```
U      uppsrc/ide/UppDlg.h
```

```
U      uppsrc/ide/ide.lay
```

The patch was created with using following command(s):

```
% cd upp-mirror
```

```
% git diff --no-color --no-prefix master | sed -e '/^index/d ; /^deleted/d' > ../uppsrc_ide.diff
```

Klugier wrote on Fri, 15 June 2018 22:42 Can you provide diff from SVN version of uppsrc instead of GIT?

I also attached `svn diff` patch to this message, just in case.

It was created with using following command (e.g. after applying the previous patch):

```
% svn diff --ignore-properties > ../uppsrc_ide_svn.diff
```

Anyway, I just showed some example(s) for this topic. It may be adapted/updated for concrete case (by developer(s)), if needed. For example, the OnBar method(s) may need changes, based on used keys.

Edit: Updated patch.

File Attachments

1) [uppsrc_ide_svn.diff](#), downloaded 264 times
