
Subject: uword table and ctrl+a (bug)

Posted by [wqcmaster](#) on Fri, 17 May 2019 11:02:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

i found a strange behaviour when selecting all (ctrl+a) in the uword editor so that just the top subtable gets selected.

Here an example file:

```
[ $$0,0#00000000000000000000000000000000:Default]
```

```
[{ }
```

```
[ {{10000 [ {{5000:5000 [s0;%% test1]
```

```
:: [s0;%% test2]]}]
```

```
:: [ {{5000:5000 [s0;%% test3]
```

```
:: [s0;%% test4]]}]
```

```
:: [ {{5000:5000 [s0;%% test5]
```

```
:: [s0;%% test6]]}]}}}]
```

I could not pinpoint the exact cause of the issue, but it goes as deep as the part (not detecting the initial table properly?)

```
const RichTxt& txt = GetConstText(anchor);
```

in the function of the TextData.cpp

```
int RichText::AdjustCursor(int anchor, int cursor) const
```

However, when i add breaklines before and after the main table it works just fine (file like this):

```
[ $$0,0#00000000000000000000000000000000:Default]
```

```
[{ }%EN-US
```

```
[s0; &]
```

```
[ {{10000 [ {{5000:5000 [s0; test1]
```

```
:: [s0; test2]]}]
```

```
:: [ {{5000:5000 [s0; test3]
```

```
:: [s0; test4]]}]
```

```
:: [ {{5000:5000 [s0; test5]
```

```
:: [s0; test6]]}]}}&]
```

```
[s0; ]]
```

Sincerly,

wqcmaster
