Subject: Deleting Ctrl from within itself
Posted by ultimatecoding on Tue, 16 Jul 2019 03:45:34 GMT
View Forum Message <> Reply to Message

Hello,

What is the correct way to make a control derived from Ctrl self-destruct? For example, when we press a button, we want that particular control to disappear and free its resources. The following code works from the parent control level but crashes the program when triggered by a child control.

```
#include <CtrlLib/CtrlLib.h>

using namespace Upp;

struct ClosableCtrl : Ctrl
{
    Button closeButton;
    int index;

    Event<> WhenClosePressed;

    ClosableCtrl(int idx) :
        index(idx)
    {
        Add(closeButton.SetLabel(AsString(idx)).HSizePos(10, 10).VSizePos(5, 5));
        closeButton.WhenPush = [=] { OnClosePressed(); };
    }

    ~ClosableCtrl()
    {
        LOG("ClosableCtrl destroyed");
    }

    virtual void Paint(Upp::Draw& w) override
    {
        w.DrawRect(GetSize(), Green());
    }

    int GetIndex() const
    {
        return index;
    }

    void SetIndex(int idx)
    {
        index = idx;
    }
```

```
    void OnClosePressed()
    {
        WhenClosePressed();
    }

};

struct CtrlPanel : Ctrl
{
    Vector<ClosableCtrl*> closableCtrls;

    CtrlPanel(int n)
    {
        for (int i = 0; i < n; ++i) {
            ClosableCtrl *cc = new ClosableCtrl(i);
            cc->WhenClosePressed = [=] { RemoveCtrl(cc->GetIndex()); };
            Add(cc->HSizePos(0, 0).TopPos(i * 100, 100));
            closableCtrls << cc;
        }
    }

    ~CtrlPanel()
    {
        for (ClosableCtrl *cc : closableCtrls) {
            delete cc;
        }
    }

    virtual void Paint(Upp::Draw& w) override
    {
        w.DrawRect(GetSize(), White());
    }

    void RemoveCtrl(int idx)
    {
        delete closableCtrls[idx];
        closableCtrls.Remove(idx);
        for (int i = 0, n = int(closableCtrls.size()); i < n; ++i) {
            closableCtrls[i]->SetIndex(i);
        }
    }
};

struct MainWindow : TopWindow
{
    CtrlPanel ctrlPanel;
```

```
    MainWindow() :
        ctrlPanel(5)
    {
        CenterScreen().Sizeable().Zoomable();
        Title("Event Test");

        Add(ctrlPanel.HSizePos(5, 5).VSizePos(5, 5));
        ctrlPanel.RemoveCtrl(1); // This works
    }
};

GUI_APP_MAIN
{
    MainWindow mainWin;
    mainWin.Run();
}
```

If I press one of the buttons, a read access violation error is thrown at

```
Ctrl *Ctrl::GetTopCtrl()
{
 GuiLock __;
 Ctrl *q = this;
 while(q->parent)
  q = q->parent;
 return q;
}
```

Also, what is the best way to store multiple controls dynamically in cases like this? According to my understanding of https://www.ultimatepp.org/www$uppweb$overview_en-us.html, it is not required that an element have a copy constructor, but when I try things like Vector<ClosableCtrl> or Array<ClosableCtrl>, I keep getting errors related to copy constructors.

Thank you.
