
Subject: Re: New experimental Linux/FreeBSD release

Posted by [amrein](#) on Sat, 11 Apr 2020 08:01:04 GMT

[View Forum Message](#) <> [Reply to Message](#)

Little fix for your Makefiles

Summary:

- * replace hard coded reference of .cache/upp.out by \$(UPPOUT)
- * secure the line that remove \$(UPPOUT) (clean target)
- * remove unneeded line, the last line that remove build_info.h (this file is in \$(UPPOUT))

Here is the patch. Of course, you will certainly fix umk/theide code instead I guess.

```
$ diff Makefile Makefile.ide
3,4c3,4
< UPPOUT = .cache/upp.out/
< CINC  = -I$(UPPDIR1)`pkg-config --cflags freetype2` `pkg-config --cflags x11` `pkg-config
--cflags fontconfig` `pkg-config --cflags xcb` `pkg-config --cflags expat` `pkg-config --cflags
xinerama` `pkg-config --cflags xrender` `pkg-config --cflags xft` `pkg-config --cflags xdmcp` 
`pkg-config --cflags xext` `pkg-config --cflags gtk+-3.0` `pkg-config --cflags libnotify` `pkg-config
--cflags libpng` -I./ -I.cache/upp.out
---
> UPPOUT = .cache/upp.out/
> CINC  = -I$(UPPDIR1)`pkg-config --cflags freetype2` `pkg-config --cflags x11` `pkg-config
--cflags fontconfig` `pkg-config --cflags xcb` `pkg-config --cflags expat` `pkg-config --cflags
xinerama` `pkg-config --cflags xrender` `pkg-config --cflags xft` `pkg-config --cflags xdmcp` 
`pkg-config --cflags xext` `pkg-config --cflags gtk+-3.0` `pkg-config --cflags libnotify` `pkg-config
--cflags libpng` -I./ -I$(UPPOUT)
94c94
< OutFile = ./ide
---
> OutFile = ide.out
103c103
<     echo '#define bmUSER    "'`whoami`'"') > ".cache/upp.out/build_info.h"
---
>     echo '#define bmUSER    "'`whoami`'"') > "$(UPPOUT)build_info.h"
72308,72309c72308,72309
72308,72309c72308,72309
<     if [ -d "$(UPPOUT)" ]; then rm -rf "$(UPPOUT)" ; fi
<     if [ -f build_info.h ]; then rm -f build_info.h ; fi
---
>     if [ "$(UPPOUT)" != "" -a "$(UPPOUT)" != "/" -a -d "$(UPPOUT)" ] ; then rm -fr "$(UPPOUT)"
; fi
>
```
