

---

Subject: \*Hold() mouse events only work for widgets at top-left corner

Posted by [Tom1](#) on Thu, 08 Apr 2021 08:53:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

E.g. LeftHold() mouse event only works for widgets at top-left corner of the window. (The same issue can be seen in both Windows and GTK/Linux.) I tracked down the code and found that sDistMax() comparison of leftmousepos and mousepos are incompatible in a way that leftmousepos is window client area related and mousepos is widget related. Therefore, comparison fails and not LeftHold() is never called:

```
void Ctrl::LHold() {
    GuiLock __;
    if(sDistMax(leftmousepos, mousepos) < GUI_DragDistance() && repeatTopCtrl &&
    GetMouseLeft())
        repeatTopCtrl->DispatchMouseEvent(LEFTHOLD, repeatMousePos, 0);
}
```

EDIT: Would this be a correct fix?

```
void Ctrl::LHold() {
    GuiLock __;
    if(sDistMax(leftmousepos, mousepos + mouseCtrl->GetRect().TopLeft()) < GUI_DragDistance()
    && repeatTopCtrl && GetMouseLeft())
        repeatTopCtrl->DispatchMouseEvent(LEFTHOLD, repeatMousePos, 0);
}
```

The same issue applies to RightHold() and MiddleHold().

Best regards,

Tom

---