
Subject: App "swallowing" mouseclicks
Posted by [peterh](#) on Tue, 30 Aug 2022 04:21:54 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi I compiled the tutorial sample "Gui21" "creating and using custom widgets". It derives a widget from "Ctrl".

Just the code as a reminder:

```
struct MyCtrl : public Ctrl {  
    int count = 0;  
  
    virtual void Paint_Draw&(w) override {  
        w.DrawRect(GetSize(), White());  
        w.DrawText(2, 2, AsString(count));  
    }  
  
    virtual void LeftDown(Point, dword) override {  
        count++;  
        Refresh();  
    }  
};
```

I made then an experimental program, deriving not from "Ctrl", but deriving from "EditString". Using this, I noticed, it does pretty often "swallow" mouseclicks, this means it does not react to them.

Then I tried the original code again and this "swallows" mouseclicks too, not so often but randomly about 1 out of 10 clicks.

It happens (reliably) both in debug and release mode.
I am on nightly build 16323, Win10 64 bit, using Clang 64 bit.

The computer is pretty fast, Ryzen 7 and CPU load in Task Manager is close to zero on all 16 cores.

Testproject code:

Main:
`#include <CtrlLib/CtrlLib.h>`

`using namespace Upp;`

```
struct MyCtrl : public EditString {  
    int count = 0;  
  
    virtual void Paint_Draw&(w) override {  
        //w.DrawRect(GetSize(), White());  
        EditString::Paint(w);
```

```

w.DrawText(2, 2, AsString(count));
}

virtual void LeftDown(Point p, dword d) override {
    count++;
    //Refresh();
    EditString::LeftDown(p,d);
}
};

#define LAYOUTFILE <Gui21/Gui21.lay>
#include <CtrlCore/lay.h>

struct Gui21 : public WithGui21Layout<TopWindow> {
    Gui21();
};

Gui21::Gui21()
{
    CtrlLayout(*this, "Window title");
}

GUI_APP_MAIN
{
    Gui21().Run();
}

CtrlLib.usc
ctrl MyCtrl {
    >EditString;
}
Gui21.lay
LAYOUT(Gui21Layout, 216, 144)
ITEM(MyCtrl, myctrl, Tip(t_("Test")).LeftPosZ(44, 120).TopPosZ(36, 52))
ITEM(Upp::EditString, dv___1, LeftPosZ(44, 64).TopPosZ(96, 19))
END_LAYOUT

```

It "swallows" fast mouseclick sequences preferably.

Edit:

I believe, I know the reason: EditString "swallows" clicks, when it detects a double click.
