

---

Subject: Re: Name of a print job is missing  
Posted by [mirek](#) on Mon, 13 Nov 2006 10:49:29 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

OK this seem to work fine for all cases:

```
bool PrinterJob::Execute0(bool dodlg)
{
    pdlg = new Win32PrintDlg_;
    PRINTDLG& dlg = *pdlg;
    dlg.Flags =
        PD_DISABLEPRINTTOFILE|PD_NOSELECTION|PD_HIDEPRINTTOFILE|PD_RETURNDEFAULT;
    dlg.nFromPage = current;
    dlg.nToPage = current;
    dlg.nMinPage = from;
    dlg.nMaxPage = to;
    if(from != to)
        dlg.Flags |= PD_ALLPAGES;
    dlg.hwndOwner = GetActiveWindow();
    dlg.Flags |= PD_RETURNDEFAULT;
    if(!PrintDlg(&dlg)) return false;
    if(dlg.hDevMode) {
        DEVMODE *pDevMode = (DEVMODE*)::GlobalLock(dlg.hDevMode);
        pDevMode->dmOrientation = landscape ? DMORIENT_LANDSCAPE : DMORIENT_PORTRAIT;
        ::GlobalUnlock(dlg.hDevMode);
    }
    HDC hdc;
    if(dodlg) {
        dlg.Flags =
            PD_DISABLEPRINTTOFILE|PD_NOSELECTION|PD_HIDEPRINTTOFILE|PD_RETURNDC;
        if(!PrintDlg(&dlg)) return false;
        hdc = dlg.hDC;
    }
    else {
        DEVNAMES *p = (DEVNAMES *)::GlobalLock(dlg.hDevNames);
        String driver = (const char *)p + p->wDriverOffset;
        String device = (const char *)p + p->wDeviceOffset;
        if(dlg.hDevMode) {
            DEVMODE *pDevMode = (DEVMODE*)::GlobalLock(dlg.hDevMode);
            hdc = CreateDC(driver, device, NULL, pDevMode);
            ::GlobalUnlock(dlg.hDevMode);
        }
        else
            hdc = CreateDC(driver, device, NULL, NULL);
    }
    if(dlg.hDevMode)
```

```

::GlobalFree(dlg.hDevMode);
if(dlg.hDevNames)
::GlobalFree(dlg.hDevNames);
if(hdc) {
    draw = new PrintDraw(hdc, Nvl(name, Ctrl::GetAppName()));
    page.Clear();
    if(!(dlg.Flags & PD_PAGENUMS)) {
        dlg.nFromPage = dlg.nMinPage;
        dlg.nToPage = dlg.nMaxPage;
    }
    for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? dlg.nCopies : 1); c++)
        for(int i = dlg.nFromPage - 1; i <= dlg.nToPage - 1; i++)
            for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? 1 : dlg.nCopies); c++)
                page.Add(i);
    return true;
}
return false;
}

```

testcase (puttin' that to reference):

```

#include <CtrlLib/CtrlLib.h>

GUI_APP_MAIN
{
    PrinterJob pj;
    if(PromptYesNo("Landscape?"))
        pj.Landscape();
    if(!PromptYesNo("Use default printer?"))
        pj.Execute();
    Draw& w = pj;
    w.StartPage();
    w.DrawText(0, 0, "Hello world!", Roman(100));
    w.EndPage();
}

```

Mirek

---