Subject: HttpClient logs in Release mode
Posted by hojtsy on Mon, 30 Jan 2006 16:33:29 GMT
View Forum Message <> Reply to Message

It seems that HttpClientGet creates long entries in the logfile even if I compile in Release mode. I would like to avoid creating a logfile when everything works OK. Logfile looks like this:

```
HttpClient::Execute
 socket host = something:8080
 [01/30/2006 17:32:23 @ 906] Socket::Data::OpenClient(something:8080, timeout 0, block false)
 [01/30/2006 17:32:23 @ 906] Socket::Data::Close(-1, timeout = 0)
 [01/30/2006 17:32:23 @ 906] //Socket::Data::Close, ok = false
 [01/30/2006 17:32:23 @ 906] Socket::Data::Open() -> 168
 [01/30/2006 17:32:23 @ 906] NoDelay(168)
 host = something, port = 8080
 request: GET something HTTP/1.1
 URL: http://something
 Host: something
 Connection: close
 Accept: */*
 Agent: Ultimate++ HTTP client


 [01/30/2006 17:32:23 @ 921] WriteWait(@ 168: 222, Tmax = 1000)
 [01/30/2006 17:32:23 @ 921] //WriteWait() -> 222
 [01/30/2006 17:32:24 @ 1171] recv(168) -> 268
 [01/30/2006 17:32:24 @ 1171] recv(168) -> 3659
 [01/30/2006 17:32:24 @ 1171] recv(168) -> 0
 [01/30/2006 17:32:24 @ 1171] Socket::Data::Close(168, timeout = 0)
 [01/30/2006 17:32:24 @ 1171] Socket::Data::CloseRaw(168)
 [01/30/2006 17:32:24 @ 1171] //Socket::Data::CloseRaw, ok = true
 [01/30/2006 17:32:24 @ 1171] //Socket::Data::Close, ok = true
//HttpClient::Execute
TIMING Socket::Data::Read:   0.0 us -   0.0 us (  0.0 us / 14 ), min:   0.0 us, max:   0.0 us, nesting:
1 - 14
TIMING Socket::Data::PeekRead:   2.6 s  - 173.7 ms (  2.6 s  / 15 ), min:   0.0 us, max:   1.0 s ,
nesting: 1 - 15
TIMING Socket::Data::Write: 999.4 us - 199.9 us (  1.0 ms / 5 ), min:   0.0 us, max:   1.0 ms,
nesting: 1 - 5
TIMING Socket::Data::PeekWrite: 998.9 us -  99.9 us (  1.0 ms / 10 ), min:   0.0 us, max:   1.0 ms,
nesting: 1 - 10
```