
Subject: Re: Upp 2007.1beta3 released
Posted by [ebojd](#) on Thu, 01 Feb 2007 20:47:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

BTW, appended is some hacks to the head Makefile that might be useful... These were convenience hacks to make the old SVN source to compile and install easy.

EBo --

```
### export UPPOUT = out/
# EBo -- try explicit paths
export UPPOUT = $(shell pwd)/out/
export OutFile = $(UPPOUT)ide/GCC-Gcc-Gui-Linux-Main-Shared/ide

# EBo -- Allow admins to set the destination directory to something
# more reasonable (like "/usr/local/" instead of "/usr/local/usr/")
# which is used to do. "/usr" may be preferred.
ifeq ($(DESTDIR),)
    DESTDIR = /usr/local
endif

.PHONY: theide
theide:
    $(MAKE) -f uppsrc/ide/Makefile

# EBo -- making theide separate from install will allow users to
# build and test without root access.
.PHONY: all
all: theide # install clean

# EBo -- install (-D) will create the appropriate parent directories
#
# mkdir -p $(DESTDIR)/bin
# mkdir -p $(DESTDIR)/share/applications
# mkdir -p $(DESTDIR)/share/pixmaps
# mkdir -p $(DESTDIR)/share/upp
.PHONY: install
install:
    install -D $(OutFile) $(DESTDIR)/bin/theide
    install -D uppsrc/ide/theide.desktop $(DESTDIR)/share/applications/theide.desktop
    install -D uppsrc/ide/theide-48.png $(DESTDIR)/share/pixmaps/theide.png
    install -D uppsrc/ide/GCC.bm $(DESTDIR)/share/upp
    cp -r Common $(DESTDIR)/share/upp
    cp -r uppsrc $(DESTDIR)/share/upp
    cp -r examples $(DESTDIR)/share/upp
```

```
cp -r reference $(DESTDIR)/share/upp  
cp -r tutorial $(DESTDIR)/share/upp
```

.PHONY: clean

clean:

```
${RM} -r $(UPPOUT)
```

Remove all public traces...

uninstall:

```
${RM} $(DESTDIR)/bin/theide
```

```
${RM} $(DESTDIR)/share/applications/theide.desktop
```

```
${RM} $(DESTDIR)/share/pixmaps/theide.png
```

```
${RM} -r $(DESTDIR)/share/upp
```