

---

Subject: Re: Upp 2007.1rc4 released

Posted by [fallingdutch](#) on Tue, 03 Apr 2007 05:41:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Good Morning,

ebojd wrote on Mon, 02 April 2007 15:02: I pulled a bonehead yesterday when I wrote the upp-portage ebuild for rc4 and just removed the old rc3 before testing rc4... DOH.

Here is a patch for the top Makefile and some questions for the uppsrc/ide/Makefile.

\*) is there a reason why pkg-config was not used in the uppsrc/ide/Makefile instead of hardcoding?

the uppsrc/ide/Makefile is a slightly changed Makefile which was generated by theide and theide hardcodes it.

ebojd wrote on Mon, 02 April 2007 15:02

Top level Makefile:

\*) move all: before theide: -- if no arguments are given to make, it will run the first one which is assumed to be all.

yes, sounds good.

ebojd wrote on Mon, 02 April 2007 15:02

\*) added -i in front of install so that it will deal appropriately with files that already exist, etc.

what did you do? don't see the change in the patch either.

ebojd wrote on Mon, 02 April 2007 15:02

\*) added trailing / to all install (cp -r \*) lines. I do not know where the bug is, but it will sometimes install the files in a directory one above the destination.

yes, thought they have been there as you see the install lines.

ebojd wrote on Mon, 02 April 2007 15:02

\*) remove clean from all -- because the "make all" and "make install" are separate.

ok

ebojd wrote on Mon, 02 April 2007 15:02

\*) added mkdir -p before copying Common and other files. "cp -r Common /usr/share/upp" will not copy the Common directory into /usr/share/upp but its contents.

yes sure makes sense

ebojd wrote on Mon, 02 April 2007 15:02

\*) current Makefiles break gentoo's multithreaded make. I'll

have to investigate this one.

please do so, i would like the makefile to run on as many systems as possible

ebojd wrote on Mon, 02 April 2007 15:02

\*) change `$(DESTDIR)/usr/...` to `$(DESTDIR)/...` -- if the `DESTDIR` is set to `usr`, then everything is installed into `/usr/usr`.  
Destdir should be set to something reasonable like `/usr`, `/opt`, etc.

I am sorry, but that is impossible for me - the package builder asks for a `$DESTDIR` to create a temporary folder where the root directory is simulated to create the package.  
Any Idea how to get around this are welcome!

ebojd wrote on Mon, 02 April 2007 15:02

I'm currently rebuilding `upp` (hopefully for the last time), but the folling patches should be helpful.  
I'll post the new `upp-portage` as soon as I know that it builds properly and pasts the QA tests.

The patch file should be attached.

Thank you a lot for your help, will apply all patches except the ones with `$DESTDIR`

Bas

---