Subject: two state button via layout designer Posted by qwerty on Thu, 25 May 2006 08:32:46 GMT

View Forum Message <> Reply to Message

...are there chances in next releases?

Subject: Re: two state button via layout designer Posted by mirek on Thu, 25 May 2006 10:32:09 GMT

View Forum Message <> Reply to Message

It should work now?

Mirek

Subject: Re: two state button via layout designer Posted by qwerty on Thu, 25 May 2006 14:16:46 GMT

View Forum Message <> Reply to Message

You ask me?

I ask you, because I can't find that in layout designer(or I am overseeing something?)...

Subject: Re: two state button via layout designer Posted by mirek on Thu, 25 May 2006 15:30:30 GMT

View Forum Message <> Reply to Message

gwerty wrote on Thu, 25 May 2006 10:16You ask me?

I ask you, because I can't find that in layout designer(or I am overseeing something?)...

Ah... It is Option with ThreeState activated...

Mirek

Subject: Re: two state button via layout designer Posted by gwerty on Thu, 25 May 2006 16:42:15 GMT

View Forum Message <> Reply to Message

C:/MyApps/majpekidz/majpekidz.lay: In function `void InitLayout(Ctrl&, L&, D&, MajpekidzLayout__layid&) [with L = majpekidz, D = majpekidz]':
C:/upp/uppsrc/CtrlCore/TopWindow.h:210: instantiated from `void CtrlLayout(T&) [with T =

majpekidz]'

C:/upp/uppsrc/CtrlCore/TopWindow.h:218: instantiated from `void CtrlLayout(T&, const char*) [with T = majpekidz]'

C:\MyApps\maipekidz\main.cpp:270: instantiated from here

C:/MyApps/majpekidz/majpekidz.lay:34: error: 'class Pusher' has no member named 'ThreeState'

Option with ThreeState checked. Why is that? Similar error occured with SwitchImage checked...

Subject: Re: two state button via layout designer

Posted by forlano on Thu, 25 May 2006 17:11:22 GMT

View Forum Message <> Reply to Message

gwerty wrote on Thu, 25 May 2006 18:42

C:/MyApps/majpekidz/majpekidz.lay: In function `void InitLayout(Ctrl&, L&, D&,

MajpekidzLayout__layid&) [with L = majpekidz, D = majpekidz]':

C:/upp/uppsrc/CtrlCore/TopWindow.h:210: instantiated from `void CtrlLayout(T&) [with T = majpekidz]'

C:/upp/uppsrc/CtrlCore/TopWindow.h:218: instantiated from `void CtrlLayout(T&, const char*) [with T = majpekidz]'

C:\MyApps\maipekidz\main.cpp:270: instantiated from here

C:/MyApps/majpekidz/majpekidz.lay:34: error: 'class Pusher' has no member named 'ThreeState'

Option with ThreeState checked. Why is that? Similar error occured with SwitchImage checked...

Can you post the layout part of your *.lay that regard the error (CTRL+T and you see the text mode of lay file)?.

Luigi

Subject: Re: two state button via layout designer Posted by gwerty on Thu, 25 May 2006 19:09:58 GMT

View Forum Message <> Reply to Message

sure

clean new app:

LAYOUT(MyAppLayout, 200, 100)
ITEM(Option, oMyOption, SetLabel(t_("someName")).ThreeState(true).LeftPosZ(60, 42).TopPosZ(16, 15))
END_LAYOUT

compiler out:

```
----- CtrlLib ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (1 / 9)
----- CtrlCore ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (2 / 9)
----- RichText ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (3 / 9)
----- Draw ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (4 / 9)
----- Core ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (5 / 9)
----- Image ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (6 / 9)
----- plugin\png ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (7 / 9)
----- plugin\z ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (8 / 9)
----- MyApp ( GUI MAIN GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (9 / 9)
main.cpp
C:/MyApps/MyApp/MyApp.lay: In function `void InitLayout(Ctrl&, L&, D&, MyAppLayout__layid&)
[with L = MyApp, D = MyApp]':
```

C:/upp/uppsrc/CtrlCore/TopWindow.h:210: instantiated from `void CtrlLayout(T&) [with T = MyApp]'

C:/upp/uppsrc/CtrlCore/TopWindow.h:218: instantiated from `void CtrlLayout(T&, const char*) [with T = MyApp]'

C:\MyApps\MyApp\main.cpp:7: instantiated from here

C:/MyApps/MyApp/MyApp.lay:2: error: 'class Pusher' has no member named 'ThreeState' MyApp: 1 file(s) built in (0:05.73), 5735 msecs / file, duration = 5735 msecs, parallelization 0%

There were errors. (0:06.00)

have any idea?

Subject: Re: two state button via layout designer Posted by forlano on Thu, 25 May 2006 20:27:14 GMT

View Forum Message <> Reply to Message

gwerty wrote on Thu, 25 May 2006 21:09sure

clean new app:

LAYOUT(MyAppLayout, 200, 100)
ITEM(Option, oMyOption, SetLabel(t_("someName")).ThreeState(true).LeftPosZ(60, 42).TopPosZ(16, 15))
END_LAYOUT

compiler out:

```
----- CtrlLib ( GUI GCC DEBUG DEBUG_FULL BLITZ WIN32 ) (1 / 9)
```

- ----- CtrlCore (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (2 / 9)
- ----- RichText (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (3 / 9)
- ---- Draw (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (4 / 9)
- ----- Core (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (5 / 9)
- ----- Image (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (6 / 9)
- ----- plugin\png (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (7 / 9)
- ---- plugin\z (GUI GCC DEBUG DEBUG_FULL BLITZ WIN32) (8 / 9)
- ---- MyApp (GUI MAIN GCC DEBUG DEBUG_FULL BLITZ WIN32) (9 / 9) main.cpp

C:/MyApps/MyApp/MyApp.lay: In function `void InitLayout(Ctrl&, L&, D&, MyAppLayout__layid&) [with L = MyApp, D = MyApp]':

C:/upp/uppsrc/CtrlCore/TopWindow.h:210: instantiated from `void CtrlLayout(T&) [with T = MyApp]'

C:/upp/uppsrc/CtrlCore/TopWindow.h:218: instantiated from `void CtrlLayout(T&, const char*) [with T = MyApp]'

C:\MyApps\MyApp\main.cpp:7: instantiated from here

C:/MyApps/MyApp/MyApp.lay:2: error: 'class Pusher' has no member named 'ThreeState' MyApp: 1 file(s) built in (0:05.73), 5735 msecs / file, duration = 5735 msecs, parallelization 0%

There were errors. (0:06.00)

have any idea?

It is as suspected... Look this line:

C:/MyApps/MyApp/MyApp.lay:2: error: 'class Pusher' has no member named 'ThreeState'

In it the is the answer: SetLabel() return a class of type Pusher to which you can't apply the method .ThreeState().

The solution: simply remove .ThreeState in that line and use

ITEM(Option, oMyOption, SetLabel(t_("someName")).LeftPosZ(60, 42).TopPosZ(16, 15))

Then in the constructor add the line:

oMyOption.ThreeState();

and the threestate button will appear.

If you do not use SetLabel() (empty label), then the you can apply the ThreeState() method directly in the designer.

Luigi

Subject: Re: two state button via layout designer Posted by mirek on Thu, 25 May 2006 20:44:34 GMT

View Forum Message <> Reply to Message

Well, this is "hierarchy ordering bug" in .usc script, something to fix.

To explain: Those "modifieres" (like ThreeState) are methods returning *this to be able to chain them.

However, there is potential trouble, as "modifier" can be method of and return base class and then be followed by "modifier" for derived class. Means, modifiers for derived classes have to be first in .lay file... which can be specified in .usc file (file with widgets description), but sometimes is faulty.

Mirek

Subject: Re: two state button via layout designer Posted by mirek on Thu, 25 May 2006 20:51:26 GMT View Forum Message <> Reply to Message

Please try this fix:

CtrlLib/CtrlLib.usc, line 328:

```
ctrl Option {
group "Push";

Text SetLabel ? @1 "Option text";
>Base:
```

(the difference is "@1", which moves that method "to the right" after ThreeState etc...)

Mirek

Subject: Re: two state button via layout designer Posted by forlano on Thu, 25 May 2006 21:10:37 GMT View Forum Message <> Reply to Message

luzr wrote on Thu, 25 May 2006 22:51Please try this fix:

CtrlLib/CtrlLib.usc, line 328:

```
ctrl Option {
  group "Push";

Text SetLabel ? @1 "Option text";
>Base;
```

(the difference is "@1", which moves that method "to the right" after ThreeState etc...)

Mirek

Yes, it works. Now I get the sequence ITEM(Option, oMyOption, ThreeState(true).SetLabel(t_("my option")).LeftPosZ(60, 68).TopPosZ(16, 15))

That seems better as threestate works immediatly without workaround.

Luigi

Subject: Re: two state button via layout designer Posted by qwerty on Thu, 25 May 2006 21:20:52 GMT

View Forum Message <> Reply to Message

I hope I will be resolving these glitches by myself in a future

thank you very much, guys

Subject: Re: two state button via layout designer Posted by forlano on Mon, 29 May 2006 20:06:19 GMT

View Forum Message <> Reply to Message

forlano wrote on Thu, 25 May 2006 23:10

Yes, it works. Now I get the sequence

ITEM(Option, oMyOption, ThreeState(true).SetLabel(t_("my option")).LeftPosZ(60, 68).TopPosZ(16, 15))

00).10pi 032(10, 13))

That seems better as threestate works immediatly without workaround.

Luigi

Only now I've seen a bad side effect: the tabctrl and the arrayctrl are not correctly shown in the right manner in designer. Moreover both control do not shown the full list of their properties. For this reason I came back to the previous state.

Luigi

Subject: Re: two state button via layout designer Posted by mirek on Sun, 04 Jun 2006 16:34:17 GMT

View Forum Message <> Reply to Message

forlano wrote on Mon, 29 May 2006 16:06forlano wrote on Thu, 25 May 2006 23:10 Yes, it works. Now I get the sequence

 $ITEM(Option,\,oMyOption,\,ThreeState(true).SetLabel(t_("my\,\,option")).LeftPosZ(60,\,true).SetLabel(t_("my\,\,option")).LeftPosZ(60,\,true)).$

68).TopPosZ(16, 15))

That seems better as threestate works immediatly without workaround.

Luigi

Only now I've seen a bad side effect: the tabctrl and the arrayctrl are not correctly shown in the right manner in designer. Moreover both control do not shown the full list of their properties. For this reason I came back to the previous state.

Luigi

Strange, it seems ok here...

Mirek

Subject: Re: two state button via layout designer Posted by forlano on Sun, 04 Jun 2006 20:21:24 GMT

View Forum Message <> Reply to Message

luzr wrote on Sun, 04 June 2006 18:34 Strange, it seems ok here...

Mirek

This is what I see with

Text SetLabel? @1 "Option text";

and ... (see next post)

File Attachments

1) v5_1.jpg, downloaded 2016 times

Subject: Re: two state button via layout designer Posted by forlano on Sun, 04 Jun 2006 20:23:37 GMT

View Forum Message <> Reply to Message

This is what I see with

Text SetLabel ? "Option text";

File Attachments

Subject: Re: two state button via layout designer Posted by mirek on Sun, 04 Jun 2006 20:29:12 GMT

View Forum Message <> Reply to Message

forlano wrote on Sun, 04 June 2006 16:21luzr wrote on Sun, 04 June 2006 18:34 Strange, it seems ok here...

Mirek

This is what I see with

Text SetLabel ? @1 "Option text";

and ... (see next post)

Should be

Text SetLabel @1 ? "Option text";

Mirek

Subject: Re: two state button via layout designer Posted by forlano on Sun, 04 Jun 2006 21:41:50 GMT

View Forum Message <> Reply to Message

luzr wrote on Sun, 04 June 2006 22:29

Should be

Text SetLabel @1 ? "Option text";

Mirek

Opsss... Now it works. Thank you

Luigi