
Subject: [Proposal] IsDoubleWidth() implementation for double width unicode chars.
Posted by [Oblivion](#) on Mon, 18 Nov 2019 11:40:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hello,

I propose adding the below code to charsets functions.

It simplifies Eastern-Asian/CJK character handling, and seems to cover more than IsCJKIdeograph().

Code is a rip-off from Markus Kuhns wwidth() implementation. It is widely used, and doesn't seem to have a problematic license.

Other parts of the original code can be added as separate functions too, but while rendering double width characters, this function can be safely used.

```
bool IsDoubleWidth(int c)
{
    // This function is taken from Markus Kuhn's wwidth implementation.
    // For license and implementation details, see:
    // https://www.cl.cam.ac.uk/~mgk25/ucs/wcwidth.c

    return c >= 0x1100
        && (c <= 0x115F      // Hangul Jamo init. consonants
            || c == 0x2329
            || c == 0x232A
            || (c >= 0x2E80 && c <= 0xA4CF && c != 0x303F) // CJK ... Yi
            || (c >= 0xAC00 && c <= 0xD7A3) // Hangul Syllables
            || (c >= 0xF900 && c <= 0xFAFF) // CJK Compatibility Ideographs
            || (c >= 0xFE10 && c <= 0xFE19) // Vertical forms
            || (c >= 0xFE30 && c <= 0xFE6F) // CJK Compatibility Forms
            || (c >= 0xFF00 && c <= 0xFF60) // Fullwidth Forms
            || (c >= 0xFFE0 && c <= 0xFFE6)
            || (c >= 0x20000 && c <= 0x2FFFD)
            || (c >= 0x30000 && c <= 0x3FFFD)
        );
}
```

Best regards,
Oblivion
