
Subject: Rendering is different in native and cross-compiled apps

Posted by [Novo](#) on Wed, 02 Apr 2025 17:42:26 GMT

[View Forum Message](#) <> [Reply to Message](#)

MacOS 10.15. Cross-compiled against SDK 10.15 on Linux.

Example of rendering:

Example of rendering in app compiled on MacOS:

```
COMMON_FLAGS = "POSIX BSD OSX";
```

A compiler declares itself as


```
Compiler: GCC Ubuntu Clang 19.1.1 (1ubuntu1) (64 bit) (C++17)
```

Is it possible to fix that?


TIA

File Attachments

1) [Screen Shot 2025-04-02 at 12.03.33 PM.png](#), downloaded 285 times



2) [Screen Shot 2025-04-02 at 12.19.52 PM.png](#), downloaded 294 times



Subject: Re: Rendering is different in native and cross-compiled apps

Posted by [mirek](#) on Wed, 02 Apr 2025 20:39:23 GMT

[View Forum Message](#) <> [Reply to Message](#)

Relevant code CtrlCore/CocoApp.mm:98

I think there must be a problem with toolchain somehow...

Subject: Re: Rendering is different in native and cross-compiled apps

Posted by [Novo](#) on Fri, 04 Apr 2025 19:49:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

I've submitted a pull request which fixes cross-compilation for MacOS using osxcross.

It is supposed that a build method will use a compiler called

x86_64-apple-darwin19-clang++-libc++ (or similar).

o64-XXX compiler names are not supported.

Building of GUI apps depends on a tool called icnsutil which replaces the Darwin iconutil.

(Debian/Ubuntu package icnsutils)

It was currently tested only with the flag OSX.

Subject: Re: Rendering is different in native and cross-compiled apps

Posted by [Novo](#) on Sun, 13 Apr 2025 16:03:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Could you please merge this pull request?

It just enables MacOS-related code on all platforms and fixes name of a librarian. This is it. It won't break anything.

It is not very convenient to use a custom-built umk ...

TIA
