

---

Subject: different compiler produces different look? [SOLVED]

Posted by [forlano](#) on Tue, 24 Oct 2006 15:26:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

this is what I see with MSC8

and this is what I see with mingw

I used Display to set the appearance of some columns. The same program show differently the same Courier font depending by the compiler. Is this normal?

Luigi

```
struct FontDisplay : Display {
    virtual void Paint(Draw& w, const Rect& r, const Value& q,
        Color ink, Color paper, dword style) const
    {
        Font fnt = Courier(14); //Font(q, r.Height() - 2);
        String txt = AsString(q);
        w.DrawRect(r, paper);
        w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
        //w.DrawText(r.left + 2+1, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
    }
};
```

### File Attachments

---

1) [ScreenHunter\\_1.png](#), downloaded 2045 times

2) [ScreenHunter\\_2.png](#), downloaded 2076 times

---

---

Subject: Re: different compiler produces different look?

Posted by [mirek](#) on Wed, 25 Oct 2006 00:50:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Definitely a bug, either in U++ or your code, most likely uninitialized variable somewhere.

Can you create a simple testcase package?

Mirek

---

---

Subject: Re: different compiler produces different look?

Posted by [forlano](#) on Wed, 25 Oct 2006 12:19:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

luzr wrote on Wed, 25 October 2006 02:50 Definitely a bug, either in U++ or your code, most likely uninitialized variable somewhere.

Can you create a simple testcase package?

Mirek

OK.  
Luigi

---

Subject: Re: different compiler produces different look?

Posted by [forlano](#) on Wed, 25 Oct 2006 12:53:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

luzr wrote on Wed, 25 October 2006 02:50 Definitely a bug, either in U++ or your code, most likely uninitialized variable somewhere.

Can you create a simple testcase package?

Mirek

After some investigation I discovered what may be a problem in my app.  
I've one arrayctrl that uses Display in a file

```
struct FontDisplay : Display {
    virtual void Paint(Draw& w, const Rect& r, const Value& q,
        Color ink, Color paper, dword style) const
    { Font fnt = Courier(13).Bold(); //Font(q, r.Height() - 2);
      String txt = AsString(q);
      w.DrawRect(r, paper);
      w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
    }
};
```

Then in another file another arrayctrl use the almost identical Display

```
struct FontDisplay : Display {
    virtual void Paint(Draw& w, const Rect& r, const Value& q,
        Color ink, Color paper, dword style) const
    {
      Font fnt = Courier(14); //Font(q, r.Height() - 2);
```

```
String txt = AsString(q);
w.DrawRect(r, paper);
w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
}
};
```

It seems that the two Display collides in some manner. In fact if I remove one of them the look is the same with both compiler. Otherwise it is different: With MSC8 both have BOLD font; with Mingw both haven't the BOLD font. Have I use only one Display?

Is this explanation enough to let you to understand the problem? Otherwise I try to do the package.

Luigi

---

---

Subject: Re: different compiler produces different look?

Posted by [mirek](#) on Wed, 25 Oct 2006 13:07:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

forlano wrote on Wed, 25 October 2006 08:53luzr wrote on Wed, 25 October 2006 02:50Definitely a bug, either in U++ or your code, most likely uninitialized variable somewhere.

Can you create a simple testcase package?

Mirek

After some investigation I discovered what may be a problem in my app.

I've one arrayctrl that uses Display in a file

```
struct FontDisplay : Display {
virtual void Paint(Draw& w, const Rect& r, const Value& q,
                  Color ink, Color paper, dword style) const
{ Font fnt = Courier(13).Bold(); //Font(q, r.Height() - 2);
String txt = AsString(q);
w.DrawRect(r, paper);
w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
}
};
```

Then in another file another arrayctrl use the almost identical Display

```
struct FontDisplay : Display {
virtual void Paint(Draw& w, const Rect& r, const Value& q,
                  Color ink, Color paper, dword style) const
```

```
{
  Font fnt = Courier(14); //Font(q, r.Height() - 2);
  String txt = AsString(q);
  w.DrawRect(r, paper);
  w.DrawText(r.left + 2, r.top + (r.Height() - GetTextSize(txt, fnt).cy) / 2, txt, fnt, ink);
}
};
```

It seems that the two Display collides in some manner. In fact if I remove one of them the look is the same with both compiler. Otherwise it is different: With MSC8 both have BOLD font; with Mingw both haven't the BOLD font.

Have I use only one Display?

Is this explanation enough to let you to understand the problem? Otherwise I try to do the package.

Luigi

Definitely, this is the problem. Actually, this is rather a problem in C++ build process (non-U++ related). You simply cannot have to different classes with the same name. Surprisingly, there is some problem detecting this situation in linker (I am not quite sure why, Tom know that .

Moral of the story: Class name clash is problem.

Mirek

---

Subject: Re: different compiler produces different look?

Posted by [forlano](#) on Wed, 25 Oct 2006 13:42:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

luzr wrote on Wed, 25 October 2006 15:07

Definitely, this is the problem. Actually, this is rather a problem in C++ build process (non-U++ related). You simply cannot have to different classes with the same name. Surprisingly, there is some problem detecting this situation in linker (I am not quite sure why, Tom know that .

Moral of the story: Class name clash is problem.

Mirek

OK. Simply renaming one class fixed the problem. I believed that the name "FontDisplay" was same special U++ reserved name to do this special task ...

Thanks a lot.

Luigi