
Subject: HTML viewer definition

Posted by [masu](#) on Sat, 02 Dec 2006 23:40:42 GMT

[View Forum Message](#) <> [Reply to Message](#)

Do you mind adding a define HTML_VIEWER to the core package, which defines the HTML viewer (browser) for POSIX systems?

I don't have "htmlview" and changed it to firefox)

```
#if defined(PLATFORM_WIN32) && !defined(PLATFORM_WINCE)
ShellExecute(NULL, "open", url, NULL, ".", SW_SHOWDEFAULT);
#endif
#ifndef PLATFORM_POSIX
system("firefox " + url + "&");
#endif
```

Matthias

Subject: Re: HTML viewer definition

Posted by [fallingdutch](#) on Sun, 03 Dec 2006 08:28:55 GMT

[View Forum Message](#) <> [Reply to Message](#)

a ln -s firefox htmlview works, too

Bas

PS: is there a way to get the default browser on linux systems or at least using gnome/kde functions?

Subject: Re: HTML viewer definition

Posted by [guido](#) on Sun, 03 Dec 2006 11:43:20 GMT

[View Forum Message](#) <> [Reply to Message](#)

fallingdutch wrote on Sun, 03 December 2006 09:28a ln -s firefox htmlview works, too

Bas

PS: is there a way to get the default browser on linux systems or at least using gnome/kde functions?

Generally \$BROWSER environment var.

For Gnome:

gconftool-2 --get /desktop/gnome/url-handlers/http/command

Guido

Subject: Re: HTML viewer definition
Posted by [fudadmin](#) on Sat, 23 Jun 2007 00:29:42 GMT
[View Forum Message](#) <> [Reply to Message](#)

AFAIK, according to new standards it should be:

Core/App.cpp line 299

```
#ifdef PLATFORM_POSIX
    system("xdg-open " + url + "&"); //aris002 -was htmlview
#endif
?
```
