
Subject: SQL "AS" for PostgreSQL fixed
Posted by [zsolt](#) on Thu, 17 May 2007 21:45:30 GMT
[View Forum Message](#) <> [Reply to Message](#)

To be able to use SqlId::As() with PostgreSQL, you have to change Sql/SqlVal.cpp:

```
SqlCol SqlId::As(const char *as) const
{
    //return id.IsNull() ? ToString() : ToString() + SqlCase(MSSQL, " as ")(" ") + as;
    return id.IsNull() ? ToString() : ToString() + SqlCase(MSSQL | POSTGRESS, " as ")(" ") + as;
}
```

Subject: Re: SQL "AS" for PostgreSQL fixed
Posted by [mirek](#) on Fri, 18 May 2007 08:11:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

zsolt wrote on Thu, 17 May 2007 17:45To be able to use SqlId::As() with PostgreSQL, you have to change Sql/SqlVal.cpp:

```
SqlCol SqlId::As(const char *as) const
{
    //return id.IsNull() ? ToString() : ToString() + SqlCase(MSSQL, " as ")(" ") + as;
    return id.IsNull() ? ToString() : ToString() + SqlCase(MSSQL | POSTGRESS, " as ")(" ") + as;
}
```

Thank you. Also fixed SqlCol::As.

Mirek

Subject: Re: SQL "AS" for PostgreSQL fixed
Posted by [zsolt](#) on Sat, 19 May 2007 12:02:26 GMT
[View Forum Message](#) <> [Reply to Message](#)

thanks.
