
Subject: i18n

Posted by [arturbac](#) on Fri, 25 May 2007 21:15:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

2 things i found on Linux Gentoo & FreeBSD

i have at the begining of App
SetLanguage(GetSystemLNG());

If i dont have locale on OS set with above invocation of Setlanguage the Format(..) function
throws Assert

if I disable above SetLanguage, the Format for such string writes no . or , chars for double value.

```
Format( value < 0 ? "(%nl)" : "%nl", value);
```

Subject: Re: i18n

Posted by [mirek](#) on Sat, 26 May 2007 05:57:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

This should fix it:

Core/Lang.cpp 130:

```
#ifdef PLATFORM_POSIX
int GetSystemLNG() {
    static int lang;
    ONCELOCK (
        String s = Environment().Get("LANG", Null);
        lang = LNGFromText(s);
        if(!lang)
            lang = LNG_ENGLISH;
        const char *q = strchr(s, '.');
        if(q)
            lang = SetLNGCharset(lang, CharsetByName(q + 1));
    );
    return lang;
};
#endif
```

Mirek

Subject: Re: i18n
Posted by [arturbac](#) on Sat, 26 May 2007 16:01:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

This will fix the app crash , ie read beoyond the string
But I'm not sure where to search fo lack of "." or "," in double values

```
#ifdef PLATFORM_POSIX
int GetSystemLNG() {
    static int lang;
    INIT_LOCK (
        String s = Environment().Get("LANG", Null);
        if ( s.GetCount()>4 )
            lang = LNGFromText(s);
        else
            lang = LNG_ENGLISH;
        const char *q = strchr(s, '.');
        if(q)
            lang = SetLNGCharset(lang, CharsetByName(q + 1));
    );
    return lang;
};

#endif
```

Subject: Re: i18n
Posted by [mirek](#) on Mon, 28 May 2007 12:42:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

WEll, the idea of my fix was the if the language is not recognized, it is set as LNG_ENGLISH.
Have you tried that?

Subject: Re: i18n
Posted by [arturbac](#) on Tue, 29 May 2007 15:36:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
lang = LNGFromText(s);
if(!lang)
```

I got app crashed because of attempt to read beoyond the string in
LNGFromText(s);

```
i have s.GetCount() == 0;
```

```
so
int LNGFromText(const char *s)
{
    int l = 0;
    if(IsAlpha(*s)) {
```

s == NULL , and will fail , Am i right ?

Subject: Re: i18n
Posted by [mirek](#) on Tue, 29 May 2007 16:32:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Well, no. If s.GetCount() == 0, then *s == '\0'.

Not arguing with the crash, going to test it now

Mirek

Subject: Re: i18n
Posted by [mirek](#) on Tue, 29 May 2007 16:39:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

OK, just tested:

```
DUMP(LNGFromText(String()));
```

and getting 0, no crash, just as expected.

Whatever crashes for you, must be something different...

Subject: Re: i18n
Posted by [arturbac](#) on Tue, 29 May 2007 16:52:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

ONCELOCK undefined ...

```
----- UppCalc ( GUI MAIN GCC DEBUG SHARED DEBUG_FULL BLITZ LINUX ) (9 / 9)
/root/uppsrc/Core/Lang.cpp: In function 'int Upp::GetSystemLNG()':
/root/uppsrc/Core/Lang.cpp:115: error: expected primary-expression before 's'
/root/uppsrc/Core/Lang.cpp:115: error: expected `)' before 's'
/root/uppsrc/Core/Lang.cpp:116: error: 's' was not declared in this scope
```

/root/uppsrc/Core/Lang.cpp:122: error: expected primary-expression before ')' token
/root/uppsrc/Core/Lang.cpp:122: error: expected `;' before ')' token
Core: 1 file(s) built in (0:04.03), 4038 msec / file, duration = 4202 msec, parallelization 0%

There were errors. (0:06.45)

but with INIT_LOCK works

However there are still no . or , in values from double in formatted string.

Subject: Re: i18n
Posted by [mirek](#) on Tue, 29 May 2007 17:24:40 GMT
[View Forum Message](#) <> [Reply to Message](#)

ONCELOCK: Sorry, should be

ONCELOCK { }

(is "(").
