
Subject: Prefix to prevent name clash in SQL: Sqld, variables, tables, ...

Posted by [mingodad](#) on Sun, 17 Feb 2008 12:40:01 GMT

[View Forum Message](#) <> [Reply to Message](#)

Today I was converting one application to upp 2008.1 and found that the actual system of parse database schema can generate name clash:

```
TABLE_(CURRENCIES)
INT_(CURRENCY)
END_TABLE
```

The above will generate a name clash:

main.cpp

```
In file included from d:\upp\uppsrc/Sql/sch_model.h:162,
    from d:\upp\uppsrc/plugin/sqlite3/Sqlite3Schema.h:82,
    from d:\upp\uppsrc/Sql/sch_header.h:45,
    from d:\MyApps\DADBiz\VADABiz.h:17,
    from d:\MyApps\DADBiz\main.cpp:1:
```

```
d:\MyApps\DADBiz\dadbiz.sch:33: error: 'Upp::Sqld CURRENCY' redeclared as different kind of
symbol
```

```
d:\upp\mingw\include/oaidl.h:113: error: previous declaration of 'typedef union CY CURRENCY'
```

```
In file included from d:\upp\uppsrc/Sql/sch_model.h:162,
```

```
    from d:\upp\uppsrc/plugin/sqlite3/Sqlite3Schema.h:82,
    from d:\upp\uppsrc/Sql/sch_source.h:6,
    from d:\MyApps\DADBiz\VADABiz.h:18,
    from d:\MyApps\DADBiz\main.cpp:1:
```

```
d:\MyApps\DADBiz\dadbiz.sch:33: error: 'Upp::Sqld CURRENCY' redeclared as different kind of
symbol
```

```
d:\upp\mingw\include/oaidl.h:113: error: previous declaration of 'typedef union CY CURRENCY'
```

[FEATURE REQUEST]

So I studied the source code and end up with some modifications that allow us to specify a prefix to the generated symbols with a definition of one preprocessor macro:

```
#define SCHEMA_PREFIX_CPP _ANY_PREFIX_YOU_LIKE_
```

And after that any reference to tables or fields should be done as:

```
dbList.AddKey(_ANY_PREFIX_YOU_LIKE_CURRENCY);
dbList.SetTable(_ANY_PREFIX_YOU_LIKE_CURRENCIES);
dbList.AddColumn(_ANY_PREFIX_YOU_LIKE_CURRENCY, t_("Id"), .SetFormat("%8>d");
    dbList.SetOrderBy(_ANY_PREFIX_YOU_LIKE_CURRENCY).Limit(100);
```

It doesn't break any application that already works, because without defining SCHEMA_PREFIX_CPP all generated symbols remain as before.

In this process I've found a bug in GCC when joining string in macros, in some cases it adds a

space betwen the tokens, that's why the macro ADD_SCHEMA_PREFIX_CPP2 was created.

I've sending attached the files I've modified.

I'll hope it will be usefull to others and probably be included in the official distribution too !

Thanks for all of you that help develop this fantastic tool !

If you need more explanations, ask me !

Ps:

[FEATURE REQUEST]

As well to allow applications made with upp to work with databases, tables generated by other programs that doesn't create table and record fields names in uppercase (commonly lowercase) a patch to sql.cpp to make comparisons after convert field names retrieved from queries to uppercase.

Instead of:

```
// sql.cpp line 254
Value Sql::operator[](SqlId id) const {
    String s = ~id;
    for(int i = 0; i < cn->info.GetCount(); i++)
        if(cn->info[i].name == s)
            return operator[](i);
    return Value();
}
```

Use this :

```
Value Sql::operator[](SqlId id) const {
    String s = ~id;
    for(int i = 0; i < cn->info.GetCount(); i++)
    {
        String sb = ToUpper(cn->info[i].name);
        if(sb == s)
            return operator[](i);
    }
    return Value();
}
```

File Attachments

- 1) [sch_header.h](#), downloaded 508 times
 - 2) [sch_model.h](#), downloaded 552 times
 - 3) [sch_source.h](#), downloaded 787 times
 - 4) [Sql.cpp](#), downloaded 614 times
-

Subject: Re: Prefix to prevent name clash in SQL: SqlId, variables, tables, ...
Posted by [mirek](#) on Tue, 19 Feb 2008 22:42:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

OK, why not. Path accepted.

Only I have rather placed ToUpper to Execute -> that way we will avoid ToUpper in each row fetch... (Equality comparison is fast, ToUpper is not...):

```
bool Sql::Execute() {
    SqlSession &session = GetSession();
    if(session.traceslow < INT_MAX)
        cn->starttime = GetTickCount();
    if(session.usrlog)
        UsrLogT(9, cn->statement);
    Stream *s = session.GetTrace();
    if(s) {
#ifndef NOAPPSQL
        if(this == &AppCursor())
            *s << "SQL* ";
#endif
        *s << cn->statement << '\n';
    }
    session.GetStatus().Statement(cn->statement);
    session.PassStatus(ActivityStatus::EXECUTING);
    bool b = cn->Execute();
    session.GetStatus().Time(GetTickCount() - cn->starttime);
    session.PassStatus(ActivityStatus::END_EXECUTING);
    if(!b) {
        if(s) {
            *s << "## ERROR: " << session.GetLastError() << '\n';
        }
        session.GetStatus()
            .Error(session.GetLastError())
            .ErrorCode(session.GetErrorCode())
            .ErrorCode(session.GetErrorCodeString());
        session.PassStatus(ActivityStatus::EXECUTING_ERROR);
    }
    for(int i = 0; i < cn->info.GetCount(); i++)
        cn->info[i].name = ToUpper(cn->info[i].name);
    return b;
}
```

(please check)

BTW, was your suggestion based on real problems or do you just want to play safe?

Mirek

Subject: Re: Prefix to prevent name clash in SQL: Sqlld, variables, tables, ...
Posted by [WebChaot](#) on Wed, 30 Jul 2008 15:57:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi Mirek!

I found this article in forum related to my current problem:

I need to create grids (arrayctrl) via database tables. But because of these lines

```
for(int i = 0; i < cn->info.GetCount(); i++)  
cn->info[i].name = Toupper(cn->info[i].name);
```

i allways get the column headers in upper case. Is it possible to put switch to suppress this auto-uppercase functionality?

WebChaot

Subject: Re: Prefix to prevent name clash in SQL: Sqlld, variables, tables, ...
Posted by [mirek](#) on Fri, 01 Aug 2008 08:07:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

WebChaot wrote on Wed, 30 July 2008 11:57Hi Mirek!

I found this article in forum related to my current problem:

I need to create grids (arrayctrl) via database tables. But because of these lines

```
for(int i = 0; i < cn->info.GetCount(); i++)  
cn->info[i].name = Toupper(cn->info[i].name);
```

i allways get the column headers in upper case. Is it possible to put switch to suppress this auto-uppercase functionality?

WebChaot

Hm, I am afraid it is not the right approach.

Maybe we could add the name in the "original form" to ColumnInfo?

Mirek

Subject: Re: Prefix to prevent name clash in SQL: Sqld, variables, tables, ...

Posted by [sevenjay](#) on Mon, 30 Aug 2010 13:45:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

I have another opinion on this.

When you create tables/columns with lower-case names, set Sqld like

Sqld TITLE("Title");

It will not match the table/column name "Title" because it will be "TITLE" in cn->info[i].name.

That is not convenient to force user to set Sqld all upper case.

Sqld TITLE("TITLE");

I think it could be case insensitive equality comparison.

if(cn->info[i].name == s)

could be

if(0 == s.CompareInsensitive(~(cn->info[i].name)))

The method CompareInsensitive maybe like this

template <class B>

int AString::CompareInsensitive(const tchar *b) const

{

const tchar *a = B::Begin();

const tchar *ae = End();

for(;;)

if(a >= ae)

return *b == 0 ? 0 : -1;

if(*b == 0)

return 1;

int q = cmpval__(*a) - cmpval__(*b);

if((cmpval__('a') < cmpval__(*a) && cmpval__(*a) < cmpval__('z')) ||

(cmpval__('A') < cmpval__(*a) && cmpval__(*a) < cmpval__('Z')))

if(q == cmpval__('a') - cmpval__('A') || q == cmpval__('A') - cmpval__('a'))

q = 0;

if(q)

return q;

*a++;

*b++;

}

}

I tried it's OK.

But I am not sure if it is faster than ToUpper.
