

---

Subject: Bug in PrinterJob class?!

Posted by [alex100](#) on Sat, 08 Mar 2008 09:44:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello all,

I was trying to print the contents of a RichEdit Control (in a form) without showing the printer dlg and for that I created the method:

```
bool PrinterJob::ExecuteNoDlg()
{
    return Execute0(false);
}
```

And nothing was printed.

There is a method called

```
bool PrinterJob::Execute()
{
    return Execute0(true);
}
```

that prints showing the printer dlg. In my opinion this method must have optional argument to be possible to choose if one wants to show the printer dialog or not:

```
bool Execute(bool bShow=true);
```

But lets forget this method and concentrate focus on the

bool PrinterJob::Execute0(bool dodlg) method:

As dlg.nCopies is not initialized when the pronted dlg is not showed:

```
if(dodlg)
{
    dlg.Flags = PD_DISABLEPRINTTOFILE|PD_NOSELECTION|PD_HIDEPRINTTOFILE|PD_R
    ETURNDC;
    if(!PrintDlg(&dlg)) return false;
    hdc = dlg.hDC;
}
else
{
```

The dlg.nCopies remains with the value zero and in the code:

```
for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? dlg.nCopies : 1); c++)
```

```
for(int i = dlg.nFromPage - 1; i <= dlg.nToPage - 1; i++)  
for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? 1 : dlg.nCopies); c++)  
page.Add(i);
```

the page.Add(i); instruction is never executed. Thus, in function:

```
void Print(Draw& w, const RichText& text, const Rect& page, const Vector<int>& pg)
```

the for(int pi = 0; pi < pg.GetCount(); pi++) cicle is never executed even rich edit control has lots of pages.

To fix this I initialized the variable

```
dlg.nCopies=1;
```

On the beginning of the bool PrinterJob::Execute0(bool dodlg) method.

What do you think?

Alex

---

Subject: Re: Bug in PrinterJob class?!  
Posted by [mirek](#) on Sat, 08 Mar 2008 16:03:15 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

alex100 wrote on Sat, 08 March 2008 04:44Hello all,

I was trying to print the contents of a RichEdit Control (in a form) without showing the printer dlg and for that I created the method:

```
bool PrinterJob::ExecuteNoDlg()  
{  
    return Execute0(false);  
}
```

And nothing was printed.

There is a method called

```
bool PrinterJob::Execute()  
{
```

```

return Execute0(true);
}

```

that prints showing the printer dlg. In my opinion this method must have optional argument to be possible to choose if one wants to show the printer dialog or not:

```
bool Execute(bool bShow=true);
```

But lets forget this method and concentrate focus on the

bool PrinterJob::Execute0(bool dodlg) method:

As dlg.nCopies is not initialized when the pronted dlg is not showed:

```

if(dodlg)
{
dlg.Flags = PD_DISABLEPRINTTOFILE|PD_NOSELECTION|PD_HIDEPRINTTOFILE|PD_R
ETURNDC;
if(!PrintDlg(&dlg)) return false;
hdc = dlg.hDC;
}
else
{

```

The dlg.nCopies remains with the value zero and in the code:

```

for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? dlg.nCopies : 1); c++)
for(int i = dlg.nFromPage - 1; i <= dlg.nToPage - 1; i++)
for(int c = 0; c < ((dlg.Flags & PD_COLLATE) ? 1 : dlg.nCopies); c++)
page.Add(i);

```

the page.Add(i); instruction is never executed. Thus, in function:

```
void Print(Draw& w, const RichText& text, const Rect& page, const Vector<int>& pg)
```

the for(int pi = 0; pi < pg.GetCount(); pi++) cicle is never executed even rich edit control has lots of pages.

To fix this I initialized the variable

```
dlg.nCopies=1;
```

On the beginning of the bool PrinterJob::Execute0(bool dodlg) method.

What do you think?

Alex

I think we should release more often; this bug was already solved... (exactly the way you suggest). Sorry for the troubles...

Mirek

---