

---

Subject: callback1 vs callback2  
Posted by [captainc](#) on Tue, 15 Apr 2008 12:28:36 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Why can I do this:

```
void CBTestFunc2(String foo, String bar){  
    Cout() << foo << " " << bar << "\n";  
}
```

```
Callback1<String> cb1 = callback1(&CBTestFunc2, "parameter 2");  
cb1("parameter 1");
```

But not:

```
void CBTestFunc3(String one, String two, String three){  
    Cout() << Format("%s %s %s", one, two, three);  
}
```

```
Callback1<String> cb2 = callback2(&CBTestFunc3, "two", "three");  
cb2("one");
```

?

The error is: Could not deduce template argument for Upp::Callback2<P1,P2>

---

---

Subject: Re: callback1 vs callback2  
Posted by [mirek](#) on Tue, 15 Apr 2008 19:19:10 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Well, only because that parcticular kind of callback is not defined (yet).

Mirek

---

---

Subject: Re: callback1 vs callback2  
Posted by [captainc](#) on Tue, 15 Apr 2008 20:17:08 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Oh, ok. Is it an easy fix to add that capability?

---

---

Subject: Re: callback1 vs callback2  
Posted by [mirek](#) on Wed, 16 Apr 2008 07:27:52 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Well, I believe there is a related recent thread somewhere in the forum.

---

Maybe we should gather a list of missing variants first?

Mirek

---